

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 347-8)

Set a post, 5 ft. long, 6" sq. 24" in the ground, for cor. to secs. 10, 11, 14, & 15, marked T20S S11 on NE, R9W S14 on SE, S15 on SW, S10 on NW faces, with 4 notch on S & 2 notches on E edges; from which

- A fir, 42" dia., bears N.59½°E., 62 lks., mkd: T20S R9W S11 BT.
- A fir, 36" dia., bears S.86½°E., 86 lks., mkd: T20S R9W S14 BT.
- A fir, 36" dia., bears S.29°W., 54 lks., mkd: T20S R9W S15 BT.
- A fir, 15" dia., bears N.42°W., 53 lks., mkd: T20S R9W S10 BT.

GLO resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 381-2)

The point for cor. of secs. 10, 11, 14, & 15 is determined by reference to the NE & SE BTs; no other evidence of the corner fd; at exact corner point.

Set an iron post, 3 ft. long, 2" dia., 26 in the ground, for cor. of secs. 10, 11, 14, & 15, with brass cap marked:

T20S R9W
S 10 | S 11
S 15 | S 14
1921

from which

- (Old BT) A fir, 48" dia., bears N.59½°E., 62 lks., marked T20S R9W S11 BT.
- (Old BT) A fir, 40" dia., S.86½°E., 86 lks., marked T20S R9W S14 BT.
- (New BT) A fir, 12" dia., bears S.76°W., 13 lks., mkd: T20S R9W S15 BT.
- (New BT) A fir, 16" dia., bears N.28°W., 30 lks., mkd: T20S R9W S10 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12489)

The cor. of secs. 10, 11, 14, & 15, remonumented by Mensch, in 1921, with an iron post, 2" dia., 8" above ground, firmly set, with (properly marked) brass cap
from which

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 10, 11, 14, & 15

Alias	Description
Alias	Description
Alias	Description
Alias	Description

- A fir, 65" dia., bears N.59½°E., 62 lks., marked T20S R9W on bark blaze. (Thiel BT)
- A fir, 53" dia., S.86½°E., 86 lks., marked T20S R9W S14 BT on bark blaze. (Thiel BT)
- A fir, 22" dia., bears S.76°W., 13 lks., plainly blazed & healed. (Mensch BT)
- A fir, 34" dia., bears N.75½°W., 30 lks., plainly blazed & healed. (Mensch BT, record. bearing, N.28°W. I open blaze sufficiently to uncover partial marks.)
- A fir, 15" dia., bears N.35½°W., 64 lks., marked T20S R9W S10 BT. (New BT)

Fd. Ok by Les Roberts, 2/28/1983 - M93-64

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23095-6)

The cor. of secs. 10, 11, 14, and 15, monumented with an iron post, 2" dia., firmly set, projecting 7" above ground, with brass cap (properly) mkd.

from which the original bearing trees

- A fir, 63" dia, bears N.59½°E., 42.2 ft., with illegible scribe marks visible on bark blaze. (Record, 40.9 ft.)
- A fir, 61" dia, bears S.86½°E., 58.7 ft., with illegible scribe marks visible on bark blaze and an X at breast height. (Record, 56.8 ft.)

and the remains of the bearing trees mkd. by Mensch in 1921-22

- A fir stump, 31" dia, bears S.76°W., 8.6 ft. , no marks visible.
- A fir, 33" dia, bears N.75½°W., 20.7 ft., no marks visible. (Record, 19.8 ft.)

and the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54

- A fir, 20" dia, bears N.35½°W., 42.2 ft., with a healed blaze.

and a new bearing tree

- A fir, 8" dia, bears S.83°W., 34.1 ft., mkd. T20S R9W S15 BT.

An iron rod, 1/2" dia., with International Paper property sign is alongside the cor.