

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

from which
A vine maple, 6" dia., bears N.34°E., 28 lks., with partial scribe marks visible on nearly healed blaze. (Mensch BT)
An uprooted fir, 44" dia., plainly blazed & healed, the stump hole of which bears S.86°W., 27 lks. (Thiel BT)
An uprooted fir, 38" dia., plainly blazed & healed, the stump hole of which bears N.42°W., 42 lks. (Thiel BT)
Reset the iron post, now 8" above ground, & mark additional BTS as follows:
A fir, 40" dia., bears S.4¼°E., 38 lks., mkd: T20S R9W S11 BT.
A fir, 27" dia., bears S.66°45'W., 56 lks., mkd: T20S R9W S10 BT.
A fir, 28" dia., bears N.59°W., 70 lks., mkd: T20S R9W S3 BT.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23097-8)

The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with brass cap (properly) mkd.
from which the remains of an original bearing tree
A roothole bears S.86°W., 17.8 ft. with decayed fir remains alongside, no marks visible.
and the remains of a BT mkd. by Mensch in 1921-22
A roothole bears N.42°W., 27.7 ft., with a down fir stump, 36" dia, lying alongside, no marks visible.
and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54
A roothole bears S.4¼°E., 25.1 ft., with a down fir, 40" dia., alongside, no marks visible.
A roothole bears N.59°W., 46.2 ft., with a down fir, size indeterminate, alongside, no marks visible.
and new bearing trees
A chinquapin, 4" dia, bears N.78°E., 12.8 ft., mkd. X BT.
A fir, 9" dia, bears S.2½°E., 21.9 ft., mkd. T20S R9W S11 BT.
A fir, 13" dia, bears S.53°W., 3.4 ft., mkd. T20S R9W S10 BT.
A fir, 5" dia, bears N.23°W., 5.5 ft., mkd. X BT.
An iron pipe, 2" dia, firmly set, projecting 2" above ground, with concrete core cor., established by person(s) unknown, is alongside the cor.

Cont.

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor Secs 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Ronald L Rice - Oct. 2016 - Oxbow Timber 1 LLC - M172-65

Found - 1921 GLO brass cap with the following accessories:
5" Chinquapin bears N.78°E., 12.8', bark scribed visible.
13" D.Fir bears S.2½°E., 21.9', healed face.
18" D.Fir bears S.53°W., 3.4', healed face.
7" D.Fir bears N.23°W., 5.5', healed face.
2" iron pipe with concrete cor. alongside 1921 GLO corner monument. Steel post adjacent to corner.

BLM Dependent Resurvey by Jason A Lightbown, Cadastral Surveyor, Under Group No. 2841, Surveyed June/Oct. 2016 - (DCSO records Vol. 59 Page(s) 23605)

The cor. of secs. 2, 3, 10, and 11, monumented with an iron post, 2" dia., firmly set, projecting 10" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree
A roothole bears S.86°W., 17.8 ft., alongside of which is decayed fir remains, size indeterminate, no marks visible.

and the remains of a BT mkd. by Tillman and Gawron in 1953-54
A roothole bears S.4¼°E., 25.1 ft., alongside of which is a down fir, 40" dia., no marks visible.

and the BTs mkd. by Forkner in 2006-09
A chinquapin, 5" dia., bears N.78°E., 12.8 ft., with healed X visible at breast height and scribe marks BT visible on bark at base.

A fir, 13" dia., bears S.2½°E., 21.9 ft., with a healed blaze.

A fir, 18" dia., bears S.53°W., 3.4 ft., with a healed blaze.

A fir, 7" dia., bears N.23°W., 5.5 ft., with a healed blaze at breast height and at base.

A concrete-filled iron pipe, 2" dia., firmly set, projecting 2" above ground, is alongside the cor.

The geographic position in NAD 1983 (2011)
Latitude: 43°51'20.46" N Longitude: 123°44'52.64" W

Record of Survey for Roseburg Resources - Robert Ward - 11/13/2025 - M186-49

Found - 1921 GLO brass cap.
5" chinquapin bears N.78°E. 12.8' - bark scribing visible.
15" fir bears S.2½°E. 21.9' - healed face.

Continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500600

PRIMARY CORNER DESCRIPTION Cor. Secs. 2, 3, 10, & 11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

21" fir bears S.53°W. 3.4' - healed face.
9" fir bears N.23°W. 5.5' - healed face.
2" concrete filled iron pipe alongside 1921 GLO
corner monument.
Steel post adjacent to corner.