

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 500640

PRIMARY CORNER DESCRIPTION East 1/4 Cor. Sec. 3 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GL0 survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 350)</p> <p>-----</p> <p>Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which</p> <p> An alder, 6" dia., bears S.52°E., 37 lks., mkd: ¼ S BT.</p> <p> A fir, 40" dia., bears N.25°W., 28 lks., mkd: ¼ S BT.</p>
<p>GL0 resurvey by Fred Mensch, U.S. Cadastral Engineer; under Instructions dated April 8, 1920, Group 56 - (DCSO records Vol. 1 Page(s) 384-5)</p> <p>-----</p> <p>Set an iron post, 3 ft. long, 1" dia., 27" in the ground, for ¼ sec. cor. of sec. 3 only, with brass cap mkd:</p> <p style="text-align: center;">¼ S3 1921</p> <p>from which</p> <p> A fir, 40" dia., bears S.86°W., 36 lks., mkd: ¼ S3 BT.</p> <p> A fir, 36" dia., bears N.37°W., 88 lks., mkd: ¼ S3 BT.</p>
<p>Fd Ok D. Peel 6/1982 - M92-28</p>
<p>Record of Survey for Roseburg Resources - Robert Ward - 11/13/2025 - M186-49</p> <p>-----</p> <p>Found - 1921 GL0 brass cap.</p> <p> 33" metal capped fir stump bears S.30°E. 24.4' scribing visible.</p> <p> 15" fir bears N.33°E. 10.8' - tree down.</p> <p> 23" fir bears S.48½°E. 17.0' - healed face.</p> <p> 22" fir bears N.46¾°E.35.6' - healed face.</p>
<p> </p>