

PRIMARY CORNER DESCRIPTION C.C. for Secs. 2 & 3 only (North) T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 940)

I set sand stone 10x8x7 ins., 7" in the ground for closing corner to secs. 2 and 3 at point of intersection (11.25 lks. E. of cor. to secs. 34 & 35) marked with 2 notches on the E.; CC on the S.; and 4 notches on the W. faces, from which

- A Fir 30" dia., bears S.9°E., 75 lks. dist. mkd. T21S R9W S2 BT.
- A Fir 30" dia., bears S.28°W., 100 lks. dist. mkd. T21S R9W S3 BT.
- A Fir 30" dia., bears N.4°15'W., 30 lks. dist. mkd. CC T21S R9W S2 & 3 BT.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12453)

The closing cor., monumented with a sandstone, 10x8x7 ins., firmly set 6" in the ground, marked with 2 notches on E. edge, alongside which has been driven a Cedar post 4" sq., 3 ft. above ground from the sandstone the original bearing trees:

- A Fir 48" dia., bears N.4¼°E., 30 lks. dist., plainly blaze and healed. (Rec. bearing, 4¼°W.)
- A Fir 56" dia., bears S.9°E., 75 lks. dist. plainly blazed and healed.
- A Fir 60" dia., bears S.28°W., 100 lks. dist. plainly blazed and healed.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14240-41)

True point for the closing cor. of secs. 2 and 3.
Set an iron post 28" long, 2½" dia., 24" in the ground with brass cap mkd.

T 20 S R 9 W
S 35
S 3 S 2
T 21 S R 9 W
CC
1967

from which

- A Fir 55" dia., bears S.13½°E., 61 lks. dist., with healed blaze. (Orig. BT)
- A Fir snag 55" dia., bears S.32°W., 92 lks. dist., with healed blaze. (Orig. BT) (Cont. Next Page)

PRIMARY CORNER DESCRIPTION C C for Secs. 2 & 3 only (North) T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

From this point, the original closing cor. of secs. 2 & 3 bears N.0°09'W., 0.135 chs. dist., monumented with a sandstone 10x8x7 ins., firmly set 4" in the ground, mkd. with 2 notches on E. edge, from which the original bearing trees:

- A Fir snag 46" dia., bears N.4¼°E., 30 lks., with healed blaze. (Rec. N.4¼°W.)
- A Fir 55" dia., bears S.9°E., 75 lks., with healed blaze.
- A Fir snag 55" dia., bears S.28°W., 100 lks., with healed blaze.

(From this same point, the cor. of secs. 34 & 35 only bears S.89°33'W., 10.67 chs. dist.)

Dependent resurvey by Edith Forkner, Cadastral Surveyor, under Group #2286, surveyed Oct 2009 - (DCSO rec Vol 56 Pg 22328)

 The closing cor. of secs. 2 & 3, on the S bdy. of T20S R9W established by Peterson in 1966-67; monumented with an iron post, 2½" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees for the original closing cor., utilized by Peterson to reference this closing corner

- A decayed fir stump, 60" dia., bears S.13½°E., 40.3 ft., with a healed blaze.
- A decayed fir stump, 52" dia., bears S.32°W., 58.4 ft., with a healed blaze. (Record, 60.7 ft)

and new bearing trees

- A fir, 17" dia., bears S.4¼°E., 39.8 ft., mkd. T21S R9W S2 CC BT.
- A fir, 16" dia., bears S.69¼°W., 14.7 ft., mkd. T21S R9W S3 CC BT.

Corner is located on the N. end of a natural bench in a W. slope, improved in the past for use as a road. Upper edge of bench follows the line bet. secs. 2 and 3 for 1000 ft.

From this cor., a fir snag, 3 ft. dia., bears N.25°W., 20 ft. with a BLM location tag.

From this same cor., the orig. closing cor. of secs. 2 & 3, on the N. bdy. of the Tp., recovered by Tillman & Gawron in 1953-54 & utilized by Peterson in 1966-67 bears N.0°12'51"W., 8.91 ft.; monumented with a sandstone, 10x8x7", firmly set, with top flush with the surface of the ground, with marks CC on top, from which the remains of an original BT

- A decayed fir snag, 34" dia., bears N.4¼°E., 19.8 ft., no marks visible.

At the corner point

Set an iron rod, 35" long, 1/2" dia., 35" in the ground, flush with the ground surface and bury the sandstone alongside the iron rod