

PRIMARY CORNER DESCRIPTION So. 1/4 cor. for Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Les Roberts - For: International Paper Co. - March 1984 - M 96-26 and C.S. File 58/280

Found - 1954 GLO brass cap, properly mkd., set firmly in ground.

1954 BTs gone.

17" Maple stump N.58°W., 26.6 ft. (no marks) (1966 rec. N.58¼°W., 25.7 ft.)

63" Fir stump bears N.62°E., 78.5 ft., scribe visible. (1966 BT rec. N.62°E., 79.2 ft.)

42" Cedar snag S.35°W., 25.6 ft., no marks, International paper location tag nail to snag. (No rec.)

Set metal fence post beside brass cap. Wired survey attention sign to fence post.

Cor. lies on top of narrow ridge. Ridge runs N.45°E. and S.45°W. Cor. is in stand of 15-20 year old reproduction.

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - R. Smith; S. Flause, crew - April 4, 1984 - C.S. File 62/18-5

Found - 1954 GLO brass cap, properly mkd. on a 1" I.P. protruding 4" above ground.

No original evidence found.

No evidence of 1954 resurvey found.

A 1967 BLM BT, 67", now a 63", 3 ft. high Fir stump with scribing visible "¼ S35 BT", bears N.65°E., 78.5 ft. (Rec. N.62°E., 79.2 ft.)

A 1967 BLM BT, 20" now a 17", 4 ft. high Maple stump, bears N.58°W., 26.6 ft. per M 96-26 (Rec. N.58¼°W., 25.7 ft.)

New BTs- 6" D.Fir double blazed and scribed "¼ S35 CS BT", bears N.71½°E., 7.1 ft.

4" D.Fir double blazed and scribed "X BT", bears N.21°W., 5.9 ft.

Sketch in file.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2286, surveyed Oct. 2009 - (DCSO records Vol. 56 Page(s) 22329)

The ¼ sec. cor. of sec. 35 only, on the S. bdy. of T. 20 R9W reestablished by proportionate measurement by Tillman & Gawron in 1953-54, rehabilitated by Peterson in 1966-67, utilized by Roberts, in 1984, & rehabilitated by Monrean, in 1984, & by Forkner in 2006-09; monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with a brass cap (properly) mkd. continued next page

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

from which the remains of the bearing trees mkd. by Peterson
A decayed fir stump, 75" dia., bears N.62°E., 79.2 ft., no marks visible.

A decayed maple stump with sprouts, the largest of which is 7" dia., bears N.58½°W., 25.7 ft., no marks visible. and the remains of the BTs mkd. by person(s) unknown and reported by Roberts

A burned cedar snag, 40" dia., bears S.35°W., 25.6 ft., no marks visible.

and the remains of the BTs mkd. by Monrean

A fir, 9" dia., bears N.71½°E. 7.1 ft. with a healed blaze

A fir snag, 6" dia bears N.21°W. 5.9 ft with healed blaze and a bearing tree by Forkner

A hemlock, 15" dia., bears N.80°W., 42.8 ft., with scribe marks ¼ S35 BT visible on partially healed blaze and a Mag Nail on the right side center.

A steel fence post with USFS tag is alongside the cor. Corner is located, E., 70 ft., of the top of a knob, on the N. side; W., 205 ft., of a dirt road, 8 ft. wide, extending S.70°W. and E. for 95 ft. before turning S.50°E.; and W., 370 ft., of another dirt road, 8 ft. wide, extending N.15°W. and S., with a tank trap to N. and S.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23077-8)

The ¼ sec cor. of sec. 35 only, monumented with an iron post, 1" dia., firmly set, projecting 4" above ground, with brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Peterson in 1966-67

A decayed fir stump, 74" dia., bears N.62°E., 79.2 ft., with illegible scribe marks visible on badly decayed blaze.

A clump of maple trees bears N.58½°W., 25.7 ft., no marks visible.

and the remains of a bearing tree mkd. by person(s) unknown, recovered by Roberts, in 1984

A burned cedar snag, 42" dia., bears S.35°W., 25.6 ft., no marks visible.

and the remains of the bearing trees mkd. by Monrean, in 1984

A fir, 8" dia., bears N.71½°E., 7.1 ft. with a healed blaze.

A fir snag, 6" dia., bears N.21°W., 5.9 ft. with a healed blaze.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 540100

PRIMARY CORNER DESCRIPTION So. 1/4 Cor. for Sec. 35 only

| | |
|-------------|-------------------|
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |
| Alias _____ | Description _____ |

and a new bearing tree

A hemlock, 14" dia., bears N. 80° W., 42.8 ft. mkd. ¼ S35
BT.

A steel fence post with property sign is alongside the cor.