

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 26

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 352)

Set a sandstone, 12x8x6" in the ground, for ¼ sec. cor. marked ¼ on N face; raised a mound of stone, 1½ ft. high 2 ft. base, alongside. Pits impracticable. Burnt timber covering the ground.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12484-5)

Point for the ¼ sec. cor. of secs. 23 & 26, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ $\frac{S\ 23}{S\ 26}$
1954

from which

- A fir, 63" dia., bears N.68½°W., 24 lks., mkd: ¼ S23 BT.
- A fir, 36" dia., bears S.16°E., 35 lks., mkd: ¼ S26 BT.

Fd. Ok by Les Roberts, 2/27/1984 - M96-20

Douglas Co. Surveyors Office - Larry E. Monrean, Deputy - Randall W. Smith - Stephen J. Flause - 3/22/1984 - C.S. File 62/16-2

Found - 1954 US GLO brass cap on 1" IP protruding 6" above ground. Cap properly marked.

A 63" fir, now a 54" stump 3 ft. high with burnt single blaze & partial scribing visible, bears N.71°W., 16.0 ft. (1954 rec. N.68½°W., 15.8 ft.)

36" fir, now a 30" stump 4 ft. high with burnt single blaze and scribing visible "4S 26 BT" bears S.15°E. 22.6 ft (1954 rec. S.16°E. 23.1 ft)

New BTs -5" D.Fir double blazed & scribed "¼ S23 CS BT" bears N.8½°E., 21.6 ft.

4" D.Fir double blazed & scribed "¼ S26 CS BT" bears S.79½°W., 23.3 ft.

Note - See also L.D. Roberts LS #1039, survey M96-20 for condition report.

Corner lies on steep west slope of a north-south ridge covered with 10-15 year old growth.