

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 540500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 14

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 358)

-----  
Set a sandstone, 36x18x6" 24" in the ground, for 1/4 sec. cor. marked 1/4 on N face; raised a mound of stone, 1 1/2 ft. high, 2 ft. base, alongside from which

A maple, 24" dia., bears N.79 1/4°E., 102 lks., mkd: 1/4 S BT.  
A fir, 24" dia., bears S.75 1/2°E., 215 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12489)

-----  
The 1/4 sec. cor. of secs. 11 & 14, determined at rec. bearing & dist. from each of the orig. BTs, as follows:

A maple, 36" dia., bears N.79 1/4°E., 102 lks., plainly blazed & healed.

A fir, 30" dia., bears S.75 1/2°E., 215 lks., with no marks remaining.

The 1/4 sec. cor. falls at left edge of West Fork, on bare sandstone bedrock; the marked stone is not recovered.

At the corner point

Set an iron post, 8" long, 1" dia., 8" in a drill hole in solid rock, with brass cap marked:

1/4  $\frac{S\ 11}{S\ 14}$   
1953

from which new BTs

A fir, 28" dia., bears N.49°W., 102 lks., mkd: 1/4 S11 BT.

An alder, 13" dia., bears S.7°E., 99 lks., mkd: 1/4 S14 BT.

Fd. Ok by Les Roberts, 2/28/1983 - M93-64

Fd. Ok D. Branch 2/1/1987 - M101-14 & C.S. 63/48-1(C)