

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 2 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 204)

Set a Chittem post 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor. mkd. ¼ S on N. face; from which
 An Alder 10" dia., bears S.10°E., 7 lks. dist. mkd. ¼ S BT
 An Alder 12" dia., bears N.27°E., 12 lks. dist. mkd. ¼ S BT.

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO records Vol. 1 Page(s) 370)

The old ¼ sec. cor. on N. bdy. of sec. 2, T20S R9W., which is a Chittem tree, 6" dia. mkd. and witnessed as described by the surveyor general.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12458)

The ¼ sec. cor. of sec.2, marked by the remains of a Cascara stump, 6" dia., nearly rotted away, from which the remaining original bearing tree:

 An Alder 14" dia., bears N.27°E., 12 lks. dist. mkd. ¼ S BT on the bark.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 27" in the ground, with brass cap mkd:

¼ S 2
 1953

from which new bearing trees:

 A Maple 18" dia., bears S.19°E., 21 lks. dist. mkd. ¼ S2 BT.

 A Fir 48" dia., bears S.69°W., 43 lks. dist. mkd. ¼ S2 BT.

Record of Survey for Roseburg Resources - Robert Ward - 11/13/2025 - M186-49

Re-set 1953 BLM brass cap at record bearing and distance from the south ¼ corner of section 35.

Found - 14" alder bears N.27°E. 7.92' - missing.
 18" maple bears S.19°E. 13.86' - missing.
 48" fir bears S.69°W. 28.38' - down and approx. 150' down slope.

Continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 540700

PRIMARY CORNER DESCRIPTION N. 1/4 Cor. for Sec. 2 only

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

Alias _____ Description _____

New - 22" D. Fir bears S.59°W. 61.5' - blazed, scribed ¼ S2 BT
23" D. Fir bears S.62°E. 16.7' - blazed, scribed X BT
Corner falls 0.75' from the southeast side of a
22" D. Fir
Steel post adjacent to corner.