

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 578700

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only, T19-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO Survey by Henry L. Chandler, U.S. Deputy Surveyor, under Contract #705, dated April 14, 1899 - (DCSO rec Vol 1 Pg 370)

-----  
Set a post 3 ft. long, 4" sq., 24" in the ground cor. of secs.35 & 36, marked T19S S36 on NE.; and R9W S35 on NW. faces, with 1 notch on E. & 5 notches on W. edges; from which  
A Cherry 7" dia. bears N.82½°E. 30 lks mkd T19S R9W S36 BT  
A Cherry 8" dia. bears N.63°W., 22 lks mkd T19S R9W S35 BT  
Old cor. bears E. 4 lks. dist., I destroy it.  
\* 1899 survey is a corrective resurvey of Chandler's 1895 survey. The Orig. 1895 survey was not accepted but some corners were accepted on a case by case basis. Per Eugene's & Coos Bay's BLM offices.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12458-59)

-----  
The cor. of secs. 35 & 36, T19-9 determined from the remaining original bearing tree as follows:  
A Cherry snag 7" dia., bears N.82½°E., 30 lks. plainly blazed and healed.  
At the corner point  
Set an iron post 3 ft. long, 2" dia., 28" in the ground with brass cap mkd:  
T 19 S R 9 W  
S 35 | S 36  
-----  
T 20 S R 9 W  
S 2  
1953  
from which new bearing tree  
An Alder 13" dia bears N.4½°E., 55 lks mkd T19S R9W S36 BT  
A Fir 43" dia., bears N.45°W., 73 lks mkd. T19S R9W S35 BT

Ron Rice, NW Land Surveying - Jason Collver - May 2012 - C.S. File 65/76-46 & M167-71 (2/2014)

-----  
Found - 2½" GLO brass cap on iron pipe, dated 1953  
Alder 13" dia., bears N.4½°E., 55 lks. mkd. T19S R9W S36 BT. (Missing)  
Fir 43" dia., bears N.45°W., 73 lks. mkd. T19S R9W S35 BT. (Missing)  
New - 24" D. Fir bears S.7°E., 18.4 ft. blazed, scribed, T19S R9W S36 BT  
21" D. Fir bears N.67°W., 22.8 ft. blazed, scribed, T19S R9W S35 BT  
Note - Corner has steel post adjacent to it. All BTs have red painted bands and yellow tags.

Cont.

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 578700

PRIMARY CORNER DESCRIPTION Sec Cor for 35 & 36 only, T19-9

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Eugene Wobbe - Crew: Brad Foster & Matthew Ternyik - 7/7/2017  
- C.S. File 65/95-43

-----  
Found - 2½" brass cap (properly mkd) on 2" iron post with  
steel post alongside.  
24" D.Fir now 25" with healed face bears N.9°E.,  
18.4' (Rec. S.7°E.) - 2012 BT  
21" D.Fir now 22" with healed face bears N.67½°W.,  
22.8' - 2012 BT  
New - Set alum. channel marker post with BLM land survey  
marker sign North 3' from corner.  
Note - Bearings are based on 1958 BLM survey.

Douglas Co. Surveyors Office - Crew: Stephen Flause & Jeff  
Lorsung- 8/26/2021 (Filed 11/18/2021) - C.S. File 67/51-1

-----  
Found - 1954 BLM 2½" dia., brass cap on a 1" I.D. IP, proj.  
16" above ground leaning 0.5 ft. south. US GLO  
brass cap is marked as described.  
A 26" dia., D.Fir with a fully healed single blaze;  
bears N.9°E., 18.4 ft (rec. S.7°E., 18.4 ft) 2012  
A 28" dia., x 1½ ft. tall sawn D.Fir stump with the  
remains of a blaze scar and face evid inside tree  
stump bears N.65°W., 22.8 ft. (rec. N.67½°W.,  
22.8 ft.) 2012  
New - BLM land survey sign & post 3 ft. North as described  
A 22" dia., D.Fir scribed "T19S R9W S36" "CSBT" on  
a double blaze; bears S.74°E., 44.5 ft. Face is  
painted white and "BT" is painted on bark.  
A 33" dia., x 2½ ft. tall D.Fir stump with a 4" long  
MAG NAIL set over the center of the root crown;  
bears S.2°E., 4.5 ft. painted in white on east  
side of the is "LEAVE BT"  
A 4" MAG NAIL is set in top on 28" dia., stump over  
the center of the root crown N.65°W., 22.8 ft. as  
recorded.  
Note - Monuments fd plumb position is reference, monument  
is removed, then is reset at ref'd location now  
plumb and proj. 5".  
Monument is in very old regrowth forest to be logged  
soon. Mon. is near top of cutbank approx. 15 ft.  
north from center of dirt forest access rd.  
Compass decl. 15¾°E.