

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 322)

-----  
A Fir stump 4½ ft. above ground and 8" in dia., which I marked T20S S36 on NE.; R9W S1 on SE.; T21S S2 on SW.; S35 on NW. faces, with 1 notch on E. and 5 notches on W. sides, for cor. to secs. 35 & 36, 1 & 2, from which

A Fir 36" dia., bears N.80½°E., 170 lks. dist. mkd. T20S R9W S36 BT.

A Fir 36" dia., bears S.81½°E., 2.10 chs. dist. mkd. T21S R9W S1 BT.

An Alder 3" dia., bears S.60°W., 95 lks. dist. mkd. T21S R9W S2 BT.

An Alder 4" dia., bears N.5°W., 5 lks. dist. mkd. T20S R9W S35 BT.

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 1 Page(s) 368) and Vol. 3 Pg. 927)

-----  
The cor. to secs. 35 & 36, which is a Fir stump, 4½ ft. dia., mkd. T20S S36 on the NE.; R9W S1 on the SE.; T21S S3 on the SW.; and S35 on the NW. faces. I obliterated marks on the SE. and SW. faces, from which

A Fir 36" dia., bears N.81°E., 232 lks. dist. mkd. T20S R9W S36 BT.

A Fir 36" dia., bears S.81°30'E., 177 lks. dist. mkd. T21S R9W S1 BT.

An Elder 5" dia., bears N.12°W., 8 lks. dist., mkd. T20S R9W S35 BT.

The bearing tree in sec. 2 had been destroyed.  
The above bearing trees do not agree with notes furnished me by the U.S. Surveyor General.

Oct. 9, 1894

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12453-54)

-----  
The cor. of secs. 35 & 36, marked by the shell of a Fir stump, 18" dia., nearly rotted away, from which the remaining original bearing trees:

A Fir snag 38" dia., bears N.81½°E., 232 lks. dist. plainly blazed and healed. (Thiel record, bears N.80½°E., 170 lks.; Gesner record, N.81°E., 232 lks. dist.)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A Fir 50" dia., bears S.81½°E., 177 lks. dist. mkd. T21S R9W BT on the bark. (Thiel record, bears S.81½°E., 210 lks.; Gesner record, bears S.81½°E., 177 lks.)  
 An Alder 23" dia., bears N.12°W., 8 lks. dist., very cleanly healed. (Thiel record, bears N.5°W., 5 lks. dist.; Gesner record, bears N.12°W., 8 lks. dist.)

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S R 9 W  
 S 35 | S 36  
 T 21 S R 9 W  
 S 2  
 1954

from which new bearing trees:

A Hemlock 14" dia., bears N.53½°E., 23 lks. dist., mkd. T20S R9W S36 BT.  
 A Hemlock 12" dia., bears N.18°W., 14 lks. dist. mkd. T20S R9W S35 BT.

BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14222)

-----  
 The sec. cor., monumented with an iron post 2" dia., extending 12" above ground, firmly set, with brass cap mkd. in 1954,

from which original bearing trees:

A burned Fir stump 38" dia., bears N.81½°E., 232 lks. dist., with no marks remaining. (Rec. N.81°E.)  
 A burned Fir stump 50" dia., bears S.81½°E., 177 lks. dist., with no marks remaining.  
 A burned Alder 25" dia., bears N.12°W., 8 lks. dist., with healed blaze.

and bearing trees mkd. by Tillman in 1954:

A burned Hemlock snag, 18" dia., bears N.53½°E., 33 lks. dist., with healed blaze. (Rec. 23 lks.)  
 A burned Hemlock snag 15" dia., bears N.18°W., 14 lks. dist. with healed blaze.

Fd. OK, Feb. 12, 1984 by L. Roberts - C.S. File 58/280 and M 96-26

Douglas Co. Surveyors Office - L.E. Monrean, Deputy - R. Smith; S. Flause, crew - April 4, 1984 - C.S. File 62/18-6

-----  
 Found - 1954 GLO brass cap, properly mkd., on a 2" I.P. protruding 12" above ground.

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only (South)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

Orig. 36" now 38" burned & rotted Fir stump, bears N.82°E., 153.5 ft. per M 96-26. (Rec. N.81½°E., 153.1 ft., 1967 BLM)  
Orig. 36" now 45", 4 ft. high Fir stump with a burned out center bears S.81°E., 118.0 ft. per M 96-26. (Rec. S.81½°E., 116.8 ft., 1967 BLM)  
No other original evidence found.  
1954 BLM BT, a 12" now 13" Hemlock stump, 1½ ft. high, with partial scribing visible, bears N.14°W., 8.8 ft., per M 96-26. (Rec. N.18°W., 9.2 ft., 1967 BLM)  
1954 BLM BT, a 14" now 18" Hemlock stump, 1 ft. high with downed BT, with scribing visible "T20S R9W", bears N.55°E., 22.1 ft. per M 96-26 (Rec. N.53½°E., 21.8 ft. per 1967 BLM)  
New BTs- 7" D.Fir double blazed and scribed "T20S R9W S36 CS BT", bears N.84½°E., 22.8 ft.  
5" D.Fir double blazed and scribed "T20S R9W S35 CS BT", bears N.21°W., 32.1 ft.  
Sketch in file.

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2286, surveyed Oct. 2009 - (DCSO records Vol. 56 Page(s) 22332)

-----  
The cor. of secs. 35 & 36 only, on the S. bdy. of T20S R9W remonumented by Tillman and Gawron in 1953-54, utilized by Peterson in 1966-67, and by Roberts, in 1984, and rehabilitated by Monrean, in 1984; monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, with a brass cap (properly) mkd.  
from which the remains of the original bearing trees  
A root hole with fir remains, size indeterminate, bears N.81½°E., 153.1 ft., no marks visible.  
A hollow decayed fir stump, 47" dia., bears S.81½°E., 116.8 ft., no marks visible.  
and the remains of the BTs mkd. by Tillman and Gawron  
A decayed hemlock pile, size indeterminate, bears N.53½°E., 21.8 ft., no marks visible. Tree is located behind an alder, 1 ft. dia., 4 ft. from bearing tree.  
A decayed hemlock pile, size indeterminate, bears N.18°W., 9.2 ft., no marks visible.  
and the bearing trees mkd. by Monrean  
A fir, 20" dia bears N.83½°E., 22.8 ft with a healed blaze  
A fir, 12" dia., bears N.23½°W., 32.3 ft., with a healed double blaze.  
A steel fence post with a USFS tag is alongside the cor.  
continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600100

PRIMARY CORNER DESCRIPTION Sec. Cor. for 35 & 36 only, (South)

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

The geographic position (NAD 1983 (CORS 96)) of the corner of sections 35 and 36, on the south boundary of T. 20 S., R. 9 W., as determined by a tie from a temporary GPS control point, established utilizing dual frequency, carrier phase GPS receivers, and processed using the National Geodetic Survey's Online Positioning User Service (OPUS), is as follows:

Latitude: 43°47'00.15"N.  
Longitude: 123°43'39.38"W.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22897)

-----  
The cor. of secs. 35 & 36 only, on the S. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 8 ins. above ground, with a bronze cap (properly) mkd. from which the remains of the original bearing trees

A root hole with fir remains, size indeterminate, bears N.81½°E., 153.1 ft., no marks visible.

A hollow decayed fir stump, 47" dia., bears S.81½°E., 116.8 ft., no marks visible.

and the remains of the BTs mkd by Tillman & Gawron in 1953-54

The remains of a decayed hemlock, size indeterminate, bears N.53½°E., 21.8 ft., no marks visible. Tree falls behind an alder, 1 ft. dia., 4 ft. from bearing tree.

The remains of a decayed hemlock, size indeterminate, bears N.18°W., 9.2 ft., no marks visible.

and the BTs mkd. by Monrean, in 1984

A fir, 20" dia., bears N.83½°E., 22.8 ft., with a healed blaze.

A fir, 12" dia., bears N.23½°W., 32.3 ft., with a healed double blaze.

A steel fence post with a USFS tag is alongside the cor., which falls 300 ft. S. of Carpenter Creek Road, graveled surface, 15 ft. wide, bears N.35°W. and S.60°E.

Latitude: 43°47'00.15"N. Longitude: 123°43'39.38"W.  
(NAD 1983 (CORS 96))