

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600140

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 35 & 36

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

. . . the cor. reestablished by proportionate measurement by Tillman and Gawron, therefore this point is accepted as the cor.; determined at record bearing and dist. from the bearing tree by Roberts

An alder, 17" dia., bears N.54°E., 20.0 ft., with illegible scribe marks visible on bark.

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 27" in the ground, with bronze cap mkd. T20S R9W

¼
S 35|S 36
2011

from which a witness cor. established by Roberts

An aluminum post, 2" dia., firmly set, projecting 8" above ground, bears N.2°03'50"E, 30.00 ft., with bronze cap mkd. INTERNATIONAL PAPER CO UNLAWFUL TO DISTURB T20S R9W W.C. S35 + S36 1984 PLS 1039 CADASTRAL SURVEY IP TIMBERLANDS. A steel fence post is alongside the witness cor. This monument now functions as a reference monument.

A fir, 16" dia., bears N.86½°W., 19.2 ft., mkd. ¼ S35 BT. Deposit a magnet in a white plastic case at the base of the stainless steel post. Drive found steel fence post alongside the cor., which falls in a creek, dry, 2 ft. wide, course N.50°W., near the W. side of the bottom of a steep-sided gully.