

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 325-6)

-----  
Set a post, 5 ft. long, 6" sq. 18" in the ground for cor. to secs. 26, 25, 35, & 36, marked T20S S25 on NE, R9W S36 on SE, S35 on SW, S26 on NW faces, with 1 notch on S & E edges; from which

A fir, 30" dia., bears N.46°E., 112 lks., mkd: T20S R9W S25 BT.

A fir, 36" dia. bears S.69°E. 17 lks. mkd: T20S R9W S36 BT

A fir, 24" dia. bears S.20°W. 69 lks. mkd: T20S R9W S35 BT

A fir, 30" dia. bears N.68°W. 17 lks. mkd: T20S R9W S26 BT and raised a mound of stone, 1½ ft. high & 2 ft. base alongside.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12462-3)

-----  
The cor. of secs. 25, 26, 35, & 36, determined from the orig. accessories, as follows:

A fir snag, 30" dia., bears N.46°E., 112 lks., with no marks remaining on burned blaze.

A rotted fir stump, 36" dia., bears S.69°E., 17 lks., with no marks remaining.

A fir snag, 24" dia., bears S.20°W., 39 lks., with no marks remaining on burned blaze.

A rotted fir stump, 30" dia., bears N.68°W., 17 lks., with no marks remaining.

A small mound of stone is found to W of corner point.

At corner point

Set an iron post, 3 ft long, 2" dia., 22" in the ground to solid rock, and in a small mound of stone, to top, with brass cap marked:

T 20 S R 9 W  
S 26 | S 25  
S 35 | S 36  
1954

from which new BTs,

A fir, 15" dia. bears N.61°E. 18 lks. mkd: T20S R9W S25 BT

A fir, 30" dia. bears S.52°E. 66 lks. mkd: T20S R9W S36 BT

A fir, 17" dia. bears S.32½°W. 59 lks. mkd: T20S R9W S35 BT

A fir, 15" dia., bears N.63½°W., 70 lks., mkd: T20S R9W S26 BT.

FD. Ok by Les Roberts, 2/27/1984 - M96-20

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	Description
Alias	Description
Alias	Description
Alias	Description

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22899)

-----  
The cor. of secs. 25, 26, 35, and 36, monumented with an iron post, 2" dia., firmly set, projecting 6" above ground, in a collar of stone, with a bronze cap (properly) mkd. from which the remains of an original bearing tree

A burned decayed fir stump, size indeterminate, bears S.69°E., 11.2 ft., no marks visible.

and the remains of the BTs mkd by Tillman & Gawron in 1953-54

A decayed fir stump, size indeterminate, bears N.61°E., 11.9 ft., no marks visible.

A decayed fir stump, 24" dia., bears S.52°E., 42.6 ft., no marks visible. (Record, 43.6 ft.)

The shell of a decayed fir stump, 19" dia., bears N.63½°W., 45.7 ft with a healed blaze. (Rec. 46.2 ft) and the bearing trees mkd. by Forkner in 2006-09

A fir, 17" dia., bears N.13½°E., 11.8 ft., with a healed blaze.

A fir, 16" dia., bears S.75°E., 27.2 ft., with a healed blaze.

A fir, 17" dia., bears S.43½°W., 36.6 ft., with a healed blaze.

A fir, 23" dia., bears N.49°W., 9.8 ft., with a healed blaze.

A steel fence post with a USFS tag is alongside the cor.

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23086-7)

-----  
The cor. of secs. 25, 26, 35, & 36, monumented with an iron post, 2" dia., firmly set, projecting 8" above ground, in a collar of stone, with brass cap (properly) mkd. from which the remains of an original bearing tree

A burned and decayed fir stump, size indeterminate, bears S.69°E., 11.2 ft., no marks visible.

and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A decayed fir stump, size indeterminate, bears N.61°E., 11.9 ft., with illegible marks visible on detached blaze.

A decayed fir stump, 26" dia., bears S.52°E., 43.6 ft. no marks visible.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600200

PRIMARY CORNER DESCRIPTION Cor. Secs. 25, 26, 35, & 36

Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____
Alias	_____	Description	_____

A shell of a decayed fir stump, 19" dia., bears N.63½°W., 46.2 ft., with illegible reverse scribe marks visible on fragment of healed blaze.  
and new bearing trees  
A fir, 15" dia., bears N.13½°E., 11.8 ft., mkd. T20S R9W S25 BT.  
A fir, 14" dia., bears S.75°E., 27.2 ft., mkd. T20S R9W S36 BT.  
A fir, 15" dia., bears S.43½°W. , 36.6 ft., mkd. T20S R9W S35 BT.  
A fir, 21" dia. bears N.49°W., 9.8 ft. mkd T20S R9W S26 BT  
A steel fence post with a property sign is alongside the cor.