TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 600340

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 23 & 24

Alias Description
Alias Description
Alias Description
Alias Description

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 354)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on W face; from which
An alder, 3" dia., bears N.47°W., 63 lks., mkd: ¼ S BT.
An alder, 4" dia., bears S.66°W., 35 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12469

Point for the ¼ sec. cor. of secs. 23 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked: ¼
S 23 | S 24
1954
from which
A hemlock, 8" dia., bears S.60°E., 45 lks., mkd: ¼ S24 BT.
A hemlock, 8" dia., bears S.31°W., 58 lks., mkd: ¼ S23 BT.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 2204)

The 1/4 sec. cor. of secs. 23 and 24, monumented with an iron post, 1" dia., firmly set, projecting 11" above ground, with a bronze cap (properly) mkd.
from which new bearing trees
A fir, 8" dia., bears S.65°E., 13.3 ft., mkd. ¼ S24 BT.
A fir, 8" dia., bears S.63½°W., 6.3 ft., mkd. ¼ S23 BT.
Corner falls 100 ft. S. of a spur, slopes E., and 515 ft. N. of a creek, 2 ft. wide, course S.65°E.