

PRIMARY CORNER DESCRIPTION Cor. Secs. 13, 14, 23, & 24

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 354)

Set a cedar post, 4 ft. long, 4" sq. 24" in the ground, for cor. to secs. 13, 14, 23, & 24, marked T20S S13 on NE, R9W S24 on SE, S23 on SW, S14 on NW faces, with 1 notch on E & 3 notches on S edges; from which

A cedar, 8" dia., bears N.6°E., 84 lks., mkd: T20S R9W S13 BT.

A cedar, 60" dia., bears S.74°E., 19 lks., mkd: T20S R9W S24 BT.

A vinemaple, 4" dia., bears S.60°W., 55 lks., mkd: T20S R9W S23 BT.

A cedar, 36" dia., bears N.77°W., 71 lks., mkd: T20S R9W S14 BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12469-70)

The cor. of secs. 13, 14, 23, & 24, determined from the orig. BTs, as follows:

A cedar, 24" dia., bears N.9½°E., 84 lks., plainly blazed & healed. (Rec. bearing N.6°E.)

An uprooted cedar, 72" dia., with blaze buried, the stump hole of which bears S.74°E., 19 lks.

A vine maple, 6" dia., bears S.60°W., 55 lks., with partial scribe marks remaining on blaze, which has been partly split off.

A cedar, 60" dia., bears N.77°W., 71 lks., marked T20S R9W S14 on unhealed blaze.

At the corner point

Set an iron post, 3 ft long, 2" dia., 28" in the ground, with brass cap marked:

T20S	R9W
<u>S 14</u>	<u>S 13</u>
S 23	S 24
1953	

from which new BTs

A cedar, 60" dia., bears S.56½°E., 64 lks., mkd: T20S R9W S24 BT.

A hemlock, 6" dia., bears S.16½°W., 71 lks., mkd: T20S R9W S23 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor Secs 13, 14, 23, & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22904)

The cor. of secs. 13, 14, 23, and 24, perpetuated by person(s) unknown; monumented with a steel fence post, firmly set, projecting 4 ft. above ground, from which the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54

A cedar stump, 47" dia., bears S.56½°E., 40.6 ft., no marks visible. (Record and slope, 42.2 ft.)

At the corner point

Set a stainless steel post, 28" long, 2½" dia., 24" in the ground, with bronze cap mkd.

T20S	R9W
S 14	S 13
S 23	S 24
2011	

from which

A W.Fir, 16" dia., bears N.51½°E., 38.5 ft., mkd. T20S R9W S13 BT.

A pistol-butt alder, 15" dia., bears S.83¼°E., 23.6 ft., mkd. T20S R9W S24 BT on bark.

An alder, 15" dia., bears S.48¾°W., 8.3 ft., mkd. T20S R9W S23 BT on bark.

A maple, 9" dia., bears N.14¼°W., 39.3 ft., mkd. T20S R9W S14 BT on bark.

Deposit a magnet in a white plastic case at the base of the stainless steel post. Reset steel fence post alongside the cor., which falls 20 ft. S. of a creek, 3 ft. wide, course E., and 300 ft. W. of the same creek, dry, 3 ft. wide, course S.85°E.