

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 357)

Set a post, 5 ft. long, 5" sq. 24" in the ground, for cor. to secs. 11, 12, 13, & 14, marked T20S S12 on NE, R9W S13 on SE, S14 on SW, S11 on NW faces, with 1 notch on E & 4 notches on S edges; from which

- A fir, 24" dia., bears N.43½°E., 26 lks., mkd: T20S R9W S12 BT.
- A fir, 33" dia., bears S.55¾°E., 27 lks., mkd: T20S R9W S13 BT.
- A fir, 30" dia. bears S.5°W. 140 lks. mkd: T20S R9W S14 BT
- A fir, 36" dia. bears N.3½°W. 55 lks. mkd: T20S R9W S11 BT

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12473)

The cor. of secs. 11, 12, 13, & 14, determined from the remaining orig. BTs as follows;

- A sawed fir stump, 30" dia., bears N.43½°E., 26 lks., marked T20S R9W S12 BT on bark blaze.
- A fir snag, 36" dia., bears S.5°W., 140 lks., marked T20S R9W S14 BT on bark blaze.
- A sawed fir stump, 40" dia., bears N.3½°W., 55 lks., with no marks remaining.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 12" in the ground to solid rock, & in a mound of stone, 3 ft. base, to top, with brass cap marked:

T20S R9W
S 11 | S 12
S 14 | S 13
1953

from which new BTs

- A fir, 8" dia., bears N.33½°E., 74 lks., mkd: T20S R9W S12 BT.
- A fir, 13" dia., bears S.54½°E., 19 lks., mkd: T20S R9W S13 BT.
- An alder, 12" dia., bears S.11°45'W., 51 lks., mkd: T20S R9W S14 BT.
- A fir, 12" dia., bears N.29¼°W., 31 lks., mkd: T20S R9W S11 BT.

continued next page

PRIMARY CORNER DESCRIPTION Cor. Secs. 11, 12, 13, & 14

Alias	Description

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2810, surveyed Sept. 2015/Jan. 2016 - (DCSO records Vol. 58 Page(s) 23453-4)

The cor. of secs. 11, 12, 13, and 14, monumented with an iron post, 2" dia., firmly set, projecting 18 ins. above ground, in a collar of stone, with a brass cap (properly) mkd. from which the remains of the original bearing trees

A decayed fir stump, 21" dia., bears N.43½°E., 17.2 ft., no marks visible.

A very decayed burned fir stump, size indeterminate, bears N.3½°W., 36.3 ft., no marks visible.

and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A roothole bears N.33½°E., 48.8 ft., alongside of which is a down decayed fir, size indeterminate, no marks visible.

A fir, 30" dia., bears S.54½°E., 12.5 ft., with a healed blaze.

An alder, 17" dia., bears S.11¾°W., 33.7 ft., with scribe marks T20S R9W S14 BT visible on bark.

A decayed fir stump, 20" dia., bears N.26¼°W., 20.5 ft., no marks visible. (Record, N.29¼°W.)

and new bearing trees

A fir, 12" dia., bears N.65°E., 24.5 ft., mkd. T20S R9W S12 BT.

A fir, 7" dia., bears N.39¾°W., 35.3 ft., mkd. X BT.

New BTs have a 2½"x¼" magnetic nail driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Aluminum angle irons were driven alongside each monument.

An aluminum fence post with a Forest Service sign is 5 ft. W. of the monument.