

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 360)

Set a post, 4 ft. long, 4" sq., 24" in the ground, for 1/4 sec. cor., marked 1/4 S on W face; from which
A fir, 36" dia., bears S.9°W., 56 lks., mkd: 1/4 S BT.
A fir, 40" dia., bears S.28°E., 54 lks., mkd: 1/4 S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12476)

The 1/4 sec. cor. of secs. 11 & 12, determined from the orig BTs as follows:

A fir snag, 40" dia., bears S.28°E., 54 lks., with only the marks BT remaining on the bark blaze.
A fir, 60" dia., bears S.9°W., 56 lks., marked 1/4 S BT on bark blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 20" in the ground to solid rock, and in a mound of stone, 3 ft. base, to top, with brass cap marked:

1/4
S 11|S 12
1953

from which new BTs

A fir, 26" dia., bears S.72 1/2°E., 47 lks., mkd: 1/4 S12 BT.
A cedar, 21" dia., bears S.33 1/2°W., 20 lks., mkd: 1/4 S11 BT.
The 1/4 sec. cor. is located at the S side of a fir stump, 8 ft. dia.

Fd. Ok by Donald Branch - For: International Paper Co. - 2/3/1987 - M101-14 - & C.S. File 63/48-1(D)

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23090)

The 1/4 sec cor. of secs 11 & 12, monumented with an iron post, 1" dia., firmly set, projecting 8" above ground, with brass cap (properly) mkd.

from which the remains of an original bearing tree

A roothole bears S.9°W., 37.0 ft. , with a down fir, 50" dia. , lying alongside, no marks visible.
and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A fir stump, 40" dia. , bears S.72 1/2°E., 31.0 ft. , with a healed blaze. continued next page

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 11 & 12

Alias	Description
Alias	Description
Alias	Description
Alias	Description

A cedar, 39" dia. , bears S.33½°W., 13.2 ft., no marks visible.
and a new bearing tree
A fir, 8" dia., bears S.87°E., 43.3 ft., mkd. ¼ S12 BT.
An aluminum fence post with a U.S. Forest Service property sign is alongside the cor.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2810, surveyed Sept. 2015/Jan. 2016 - (DCSO records Vol. 58 Page(s) 23455-6)

The ¼ sec. cor. of secs. 11 and 12, monumented with an iron post, 1" dia., firmly set, projecting 8" above a collar of stone, with a brass cap (properly) mkd. from which the remains of an original bearing tree
A roothole bears S.9°W., 37.0 ft., alongside of which is a down fir, 50" dia., no marks visible.
and the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54
A decayed fir stump, 35" dia., bears S.72½°E., 31.0 ft., with a healed blaze.
A cedar, 43" dia., bears S.33½°W., 13.2 ft., no marks visible.
and a bearing tree mkd. by Forkner in 2006-09
A fir, 14" dia., bears S.87°E., 43.3 ft., with a healed blaze.
An aluminum fence post with Forest Service sign is alongside the cor.