

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Alonzo Gesner, Deputy Surveyor, under Contract #608 -dated April 17, 1893 - (DCSO records Vol. 3 Page(s) 927-28)

Set Alder post 4½ ft. long, 4" sq., 24" in the ground on steep hill side sloping S. for closing cor. to secs. 1 & 2, mkd. CC T21S on the S.; R9W S1 on the E.; and S2 on the W. faces with 1 groove on the E. and 5 grooves on the W. sides, from which

A Fir 40" dia bears N.6°W. 69 lks mkd. CC T21S R9W S1 2 BT
A Fir 12" dia., bears S.73°E., 56 lks. mkd. T21S R9W S1 BT
A Fir 6" dia. bears S.11°30'W., 154 lks mkd T21S R9W S2 BT

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12454)

The closing cor. of secs. 1 & 2, determined at record distance from each of the original bearing trees, as follows:

A Fir 60" dia., bears N.6°E., 69 lks. dist., plainly blazed and healed. (Rec. brg. N.6°W.)
A Fir 42" dia., bears S.77¼°E., 56 lks. dist., plainly blazed and healed. (Rec. brg. S.73°E.)
A Fir 70" dia., bears S.9°45'W., 154 lks. dist., plainly blazed and healed. (Rec. brg. S.11½°W.)

At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S R 9 W
S 36
S 2 S 1
T 21 S R 9 W
C C
1954

Fd. OK and used in BLM resurvey by Peter A. Peterson, Cadastral Surveyor, under Group #'s 350 & 511, surveyed Apr. 1966/May 1967 (DCSO records Vol. 34 Page(s) 14223)

Fd. OK, Dec. 1990 - M 111-29

Dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2286, surveyed Oct. 2009 - (DCSO records Vol. 56 Page(s) 22333)

The original closing cor. of secs. 1 & 2, on the S. bdy. of T20S R9W., remonumented by Tillman & Gawron in 1953-54, utilized by Peterson in 1966-67, and by Baker, in 1990; monumented with an iron post, 2" dia., firmly set, cont.

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 612100

PRIMARY CORNER DESCRIPTION C C for Secs. 1 & 2 only, T21-9

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

projecting 14" above ground, with a brass cap (properly) mkd. from which the remains of the original bearing trees

A decayed fir stump, 60" dia., bears N.6°E., 45.5 ft., no marks visible and tailhold notch at face.

A fir, 59" dia., bears S.77¼°E., 37.0 ft., no marks visible and small tailhold notch at face.

A fir stump, 81" dia., bears S.9¾°W., 101.6 ft., with a healed blaze.

and a new bearing tree

A fir, 7" dia., bears S.47°W., 19.6 ft., mkd. X BT.

An aluminum fence post with International Paper Company sign is alongside the cor.

Corner is located on the NE. cor. of older fir reproduction, edge bears S and W, and W, 10 ft., of a spur, slopes S.5°E., and W., 95 ft., of bottom of descent, slopes S.