TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 640400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 13 & 24

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 356)

Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor., marked ¼ S on N face; and raised a mound of stone, 1½ ft. high & 2 ft. base, alongside. Pits impracticable.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12470

Point for the ¼ sec. cor. of secs. 13 & 24, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 13
S 24
1954

from which
A Fir, 67" dia., bears N.34°E., 31 lks., mkd: ¼ S13 BT.
A hemlock, 30" dia., bears S.39½°E., 83 lks. mkd: ¼ S24 BT

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22905)

The ¼ sec. cor. of secs. 13 & 24, monumented with an iron post, 1" dia., firmly set, projecting 7" above ground, with a bronze cap, oriented south, (properly) mkd.
from which the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54
A metal-capped fir stump, 65" dia., bears N.34°E., 20.5 ft., with scribe marks 13 and other illegible scribe marks visible on partially healed blaze.
and new bearing trees
A maple, 13" dia., bears S.53°W., 34.0 ft., mkd. ¼ S24 BT on bark.
A W.Fir, 12" dia., bears N.12½°W., 48.1 ft., mkd. ¼ S13 BT
A steel fence post and an iron rod are alongside the cor., which falls 70 ft. E. of a drainage, drains N.70°E., and 240 ft. W. of a creek, dry, 1 ft. wide, course N.25°E.