

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel under contract 567 dated Feb. 16, 1891 - (DCSO records Vol. 1 Page(s) 362)

-----

A vine maple, 5" dia., which I marked ¼S on N face, for ¼ sec. cor.; from which

A fir, 24" dia., bears N.34°W., 10 lks., mkd: ¼ S BT.

A fir, 27" dia., bears S.88°E., 11 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman & Joseph S Gawron, under Group # 306, Surveyed May 1953 - Oct. 1954 (DCSO recs Vol. 29 Page(s) 12478)

-----

The ¼ sec. cor. 1 & 12, determined at rec. bearing & dist. from which each of the orig. BTs, as follows:

A fir, 30" dia., bears N.34°W., 10 lks., with only the marks BT remaining on badly scaled bark blaze.

An uprooted fir, 30" dia., with no marks remaining, the stump hole of which bears S.88°E., 11 lks.

At the corner point

Set an iron post, 3 long, 1" dia., 27" in the ground, with brass cap marked:

¼  $\frac{S \ 1}{S \ 12}$

1953

from which a new BT,

A fir, 32" dia., bears S.14½°W., 35 lks., mkd: ¼ S12 BT.

Donald Branch - For: International Paper Co. - 2/3/1987 - M101-14 - & C.S. File 63/48-1(I)

-----

Found - 1" BLM cap marked "T20S R9W ¼ S1 S12 1954

22" Fir snag bears N.37°W., 6.7 ft.

21" Fir snag bears S.16°W., 23.5 ft. with bark scribing & tag.

New BTs- 8" D.Fir bears N.5°E., 14.0 ft. scribed "¼ S1 BT"

8" D.Fir bears S.8°E., 3.1 ft. scribed "¼ S12 BT"

Note: Set a 6' alum post with attention sign next to monument

FD. Ok by Wayne Donovan, 5/19/1993 - C.S. File 63/153-55

Ronald L Rice - For: Oxbow Timber 1 LLC - Mar 2015 - M169-27

-----

Found - 1953 GLO brass cap with the following accessories:

12" D.Fir staub bears N.37°W., 6.7' - no marks

18" D.Fir snag bears S.16°W., 23.5' - no marks

13" D.Fir bears N.5°E., 14.0' - healed face

13" D.Fir bears S.8°E., 3.1' - healed face

New BT - 15" D.Fir bears N.74°E. 8.7'-blazed, scribed ¼ S1 BT

Post adjacent to corner \_\_\_\_\_ CONT.

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 1 & 12

Alias	Description

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2810, surveyed Sept. 2015/Jan. 2016 - (DCSO records Vol. 58 Page(s) 23458)

-----

The ¼ sec. cor. of secs. 1 & 12, perpetuated by Branch, in 1987; further perpetuated by Rice, in 2015; monumented with an iron post, 1" dia., firmly set, projecting 2" above ground, with a brass cap (properly) mkd.

from which the remains of an original bearing tree

A decayed fir snag, 12" dia., bears N.40¾°W., 6.6 ft., no marks visible. (Record, N.34°W.)

and the remains of a bearing tree mkd. by Tillman and Gawron in 1953-54

A fir snag, 19" dia., bears S.14½°W., 23.1 ft., no marks visible.

and the bearing trees mkd. by Branch

A fir, 13" dia., bears North, 14.0 ft., with a healed blaze.

A fir, 13" dia., bears S.6¾°E., 3.2 ft., with a healed blaze.

and a bearing tree mkd. by Rice

A fir, 15" dia., bears N.75°E., 8.7 ft., with scribe marks ¼ S1 BT visible on pitched-over open blaze and a nail at the base on the right side center.

An aluminum fence post is alongside the cor.