

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 315-16)

 Fir 7" dia., for ¼ sec. cor., marked ¼ S on W. face, from which
 Fir, 5" dia., bears S.65°W., 6 lks. dist. mkd. ¼ S BT.
 Fir 8" dia., bears S.85°E., 21 lks. dist. mkd. ¼ S BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11334)

 (39.11 chs.)
 Point for witness to the ¼ sec. cor. of sec. 30.
 Set an iron post 3 ft. long, 1" dia., 28" in the ground with brass cap mkd:
 | W C
 | ¼ S 30
 1950

(39.22 chs. - N.1°27'E)
 The ¼ sec. cor. of sec. 30 monumented with a Fir stub, 14" dia., mkd. ¼ S on E. and W. faces; from which
 A Fir stub 6" dia., bears S.65°E., 7 lks. dist. with partial scribe marks uncovered. (Rec. 6 lks.)
 A Fir 12" dia., bears S.85½°E., 22 lks. dist. with old blaze healed. (Rec. S.85°E., 21 lks.)
 Fir 16" dia., bears N.33°E., 39 lks. dist. mkd. ¼ S30 BT.
 The point for cor. is occupied by a Fir stub, 14" dia., where it is impracticable to establish a permanent monument.

Survey by Les Roberts - For: International Paper Co. - March 1993 - C.S. File 63/149 and M 116-60

 Found - 1950 GLO brass cap set firmly in the ground and marked "W.C. S¼ S30". True corner bears N.1°27'E., 7.26 ft. At true corner point, I find a 14" rotted Fir stub. No marks visible.
 New - 72" alum. post w/survey monument sign attached, beside brass cap.
 8" Fir N.76°E., 5.4 ft. scribed "WC ¼ S BT"
 8" Fir S.03°W., 9.1 ft. scribed "WC ¼ S BT"
 Also found two bearing trees of true ¼ corner:
 14" Fir stump S.85°E., 14.5 ft., no marks. (1883 BT Rec. S.85½°E., 13.9 ft.)
 18" Fir stump N.33°E., 23.9 ft., scar visible. (1950 BT rec. N.33°E., 25.7 ft.)
 Painted all bearing trees red.

CONT.

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700201

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 30 only, T20-8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22901-2)

The ¼ cor. of sec. 30 only, on the W bdy. of T20S R8W bears N.1°27'E., 58.08 ft., monumented with the remains of the original cor. tree, decayed fir pieces partially buried, from which the remains of an original bearing tree

An a decayed fir stump, 10" dia., bears S.85½°E., 13.7 ft., no marks visible. (Record, 14.5 ft.)

and the remains of a bearing tree mkd. by Tillman in 1950

A decayed fir stump, 24" dia., bears N.33°E., 25.7 ft., no marks visible.

and the witness cor. to the ¼ cor. of sec. 30 only, on the W. bdy. of T20S R8W established by Tillman

An iron post, 1" dia., firmly set, projecting 13" above ground, bears S.1°27'W., 7.26 ft. with bronze cap mkd. ¼ S30 1950

from which the bearing trees to the witness cor., mkd. by Les Roberts, PLS No. 1039, in 1993

A fir, 13" dia., bears N.68½°E., 5.8 ft., with a healed blaze.

A fir, 11" dia., bears S.2¼°W., 8.7 ft., with a healed blaze.

An aluminum fence post with a "Land Survey Monument" tag is alongside the witness cor.

At the corner point

Drive an iron rod, 30" long, 5/8" dia., 30" in the center of the remains of the cor. tree, with alum. cap mkd.

T20S

R9W R8W

|¼ S 30

2011

Fd. BC & accessories as per 2011 BLM rec by D. Edwards
12/2017 - C.S. File 65/98-2