

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 316)

Set post 6" dia., 4 ft. long, with marked stone 12" in ground for cor. to secs. 19, 30, 24 and 25, marked T20S S19 on NE.; R8W S30 on SE.; R9W S25 on SW.; S24 on NW. faces, with 4 notches on N. and 2 on S. edges; from which

- Cedar 24" dia., bears N.15°E., 45 lks. dist. mkd. T20S R8W S19 BT.
- Cedar 24" dia., bears S.12°E., 60 lks. dist. mkd. T20S R8W S30 BT.
- Fir 14" dia., bears S.21°W., 71 lks. dist. mkd. T20S R9W S25 BT.
- Cedar 24" dia., bears N.29°W., 82 lks. dist. mkd. T20S R9W S24 BT.

BLM resurvey by Thomas A. Tillman, Cadastral Surveyor, under Group #297, Surveyed May 1951/Oct. 1952 - (DCSO records Vol. 27 Page(s) 11334-35)

The cor. of secs. 19 & 30, determined at the record bearing and distance from the original SW. bearing tree as follows:

A Fir 32" dia., bears S.21°W., 71 lks. dist. plainly blazed and healed.

The three Cedar bearing trees, which were evidently dead when marked, have been uprooted; these trees occupy the approx. positions in Wright's notes, but the scribe marks are weathered away.

At the corner point

Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap mkd:

T 20 S		T 20 S
R 9 W		S 19
		S 30
S 25		R 8 W
		1950

from which new bearing trees:

- A Fir 20" dia., bears N.47½°E., 30 lks. dist. mkd. T20S R8W S19 BT.
- A Fir 12" dia., bears S.58°E., 25 lks. dist. mkd. T20S R8W S30 BT.

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16711)

(Cont. Next Page)

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

The sec. cor., monumented with an iron post 2" dia., firmly set, projecting 12" above ground, with brass cap mkd. in 1950, from which bearing trees mkd. in 1950:

A Fir 34" dia., bears N.47½°E., 30 lks. dist. with healed blaze.

A Fir 17" dia., bears S.58°E., 25 lks. dist. with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

Survey by Les Roberts - For: International Paper Co. - March 1993 - C.S. File 63/149-11 and M 116-60

Found - 1950 GLO brass cap set firmly in the ground.
20" Fir S.58°W., 16.5 ft., scar visible. (1950 BT, rec. S.58°E., 16.5 ft.)
39" Fir N.47°E., 19.8 ft., scar visible. (1950 BT, rec. N.47½°E., 19.8 ft.)

New Accessory:
72" alum. post with land monument survey sign attached to, beside brass cap.
Painted all bearing trees red.
Cor. lies on W. slope about 200 ft. South of creek, flows West.

BLM remonumentation by Aaron M. Graham, Cadastral Surveyor under Group #2000, surveyed Jan./March 2005 - (DCSO rec. Vol. 55 Page(s) 21751)

The cor. of secs. 19 and 30 only, monumented with an iron post, 2" dia., firmly set, projecting 7" above the ground, with brass cap (properly) mkd.

from which an original bearing tree
A fir, 33" dia., bears S.21°W., 46.9 ft., no marks visible.

and the remains of bearing trees mkd. by Tillman in 1950
A fir, 38" dia., bears N.47½°E., 21.0 ft., with a healed blaze. (Record, 19.8 ft.)

A fir stump, 22" dia., bears S.58°E., 16.5 ft., with a healed blaze.

and a new bearing tree
A fir, 7" dia., bears S.14½°E., 10.2 ft., mkd. T20S R8W S30 BT.

There is a steel fence post and an aluminum fence post with a monument sign on it alongside the corner.
Each new bearing tree has a 2½"x ¼" magnetic nail (Mag Nail) driven at the base right side-center.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700241

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM dependent resurvey by Edith M Forkner and Aaron M. Graham, Cadastral Surveyors, under Group #2312, surveyed July/Oct. 2011 - (DCSO records Vol. 58 Page(s) 22963)

The cor. of secs. 19 & 30 only, on the W. bdy. of the Tp., monumented with an iron post, 2" dia., firmly set, projecting 14 ins. above ground, with a brass cap (properly) mkd. from which the remains of an original bearing tree

A fir, 34" dia., bears S.21°W., 46.9 ft., with a healed blaze.

and the remains of the bearing trees mkd. by Tillman in 1950

A fir, 41" dia., bears N.47½°E., 21.0 ft., with a healed blaze.

A fir stump, 22" dia., bears S.58°E., 16.5 ft., with a healed blaze.

and a bearing tree mkd. by Graham in 2005

A fir, 10" dia., bears S.14½°E., 10.2 ft., with a healed blaze.

A steel and an aluminum fence post are alongside the cor. The, ¼ sec. cor. of sec. 25 only, on the E. bdy. of T20S R9W bears S.0°32'44"E., 49.59 ft.