

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12475)

Point for the ¼ sec. cor. of sec. 13 only, at midpoint on the E. bdy. of sec. 13.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: ¼ S 13|
1954

from which

- A Hemlock 35" dia., bears S.57°45'W., 25 lks mkd. ¼ S13 BT
- A Hemlock 38" dia., bears N.16°45'W., 81 lks mkd. ¼ S13 BT

BLM Remonumentation of corner by Wm. Glenn; C. Albert White and James E. Jelley, Cadastral Surveyors, under Group #'s 350 and 635, surveyed April/May 1967 - (DCSO records Vol. 43 Page(s) 16714-15)

The ¼ sec. cor., monumented with an iron post, 1" dia., firmly set, projecting 8" above ground with brass cap mkd. in 1954, from which the original bearing trees;

- A Hemlock 37" dia., bears S.57 3/4°W., 25 lks. dist., with scribe marks ¼ S13 BT visible on open blaze.
- A Hemlock 38" dia., bears N.16 3/4°W., 81 lks. dist., with healed blaze.

Set a 5 ft. steel fence post alongside the iron post.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2313, surveyed March/Aug. 2011 - (DCSO records Vol. 58 Page(s) 22895)

The ¼ sec. cor. of secs. 13 only, on the E. bdy. of T20S R9W monumented with an iron post, 1" dia., firmly set, projecting 3" above ground, with a bronze cap (properly) mkd. from which the remains of the BTs mkd. by Tillman, et al., in 1953-54

- A hemlock snag, 38" dia., bears S.57¾°W., 16.5 ft., with scribe marks 4 S and other illegible scribe marks visible on partially healed blaze.
 - A hemlock, 42" dia., bears N.16¾°W., 52.3 ft., with a small healed blaze at breast height. (Rec. 53.5 ft.) and a bearing tree mkd. by Forkner in 2006-09
 - A fir, 11" dia., bears S.38½°W., 55.1 ft., with axe marks X at breast height and a healed blaze. (Rec. 56.3 ft)
- A bent steel fence post is alongside the cor., which falls 30 ft. S. of a creek, 1 ft. wide, course S.80°E., and 260 ft. N. of a spur, slopes N.55°E.

Cont.

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700440

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

BLM corrective remonumentation and rehabilitation of certain corners by Edith M Forkner, Cadastral Surveyor, under Group #2000, surveyed Feb. 2006/March 2009 - (DCSO records Vol. 58 Page(s) 23080-1)

The ¼ sec cor. of sec. 13 only, monumented with an iron post, 1" dia., firmly set, projecting 6" above ground, with brass cap (properly) mkd. from which the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A hemlock snag, 38" dia., bears S.57¾°W., 16.5 ft., with scribe marks ¼ S and other illegible marks visible on partially healed blaze.

A hemlock, 42" dia., bears N.16¾°W., 53.5 ft. , with a small healed blaze at breast height and axe marks 6 ft. high.

and a new bearing tree

A fir, 10" dia., bears N.38½°W., 56.3 ft., mkd. X BT.

A steel fence post is alongside the cor.

Corner is located S, 30 ft from creek, 1 ft wide, draining E