

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION C C for Secs. 12 & 13 only, (East)

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 359)

-----  
For closing cor. to secs. 12 & 13, I set a sandstone, 8x8x8 ins., 5" in the ground marked C C with 2 notches on N. and 4 notches on S. edges; and raised a mound of stone, 1½ ft. high, 2 ft. base, alongside. Pits impracticable.

BLM Resurvey by Thomas A. Tillman and Joseph S. Gawron, Cadastral Engineers, under Group #306, surveyed May 1953/Oct. 1954 - (DCSO records Vol. 29 Page(s) 12474-75)

-----  
Point for the closing cor., at proportionate distance; there is no remaining evidence of the original corner.

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd:

T 20 S	T 20 S
CC $\frac{S\ 12}{S\ 13}$	S 7
R 9 W	R 8 W
1954	

from which

A Fir 36" dia., bears N.67°W., 69 lks. dist. mkd. T20S R9W S12 CC BT.

A Fir 36" dia., bears S.53¼°W., 30 lks. dist. mkd. T20S R9W S13 CC BT.

(From this point, the ¼ sec.cor. on the W. bdy. of Sec. 7, T20S R8W, bears N.0°34'E., 1.67 chs.)

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2810, surveyed Sept. 2015/Jan. 2016 - (DCSO records Vol. 58 Page(s) 23450-1)

-----  
The closing cor. of secs. 12 & 13 only, monumented with an iron post, 2" dia., firmly set, projecting 7" above ground, with a brass cap (properly) mkd.

from which the remains of the bearing trees mkd. by Tillman and Gawron in 1953-54

A decayed fir high stump, 33" dia., bears S.53¼°W., 19.8 ft., with illegible scribe marks visible on partially healed blaze.

A decayed fir stump, 35" dia., bears N.67°W., 45.5 ft., with scribe marks 1 C T visible on open blaze. Stump is located behind a hemlock, 24" dia.

and new bearing trees

A fir, 16" dia., bears S.46°W., 26.2 ft., mkd. T20S R9W S13 CC BT and a Mag Nail at the base on the left side center.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700500

PRIMARY CORNER DESCRIPTION C.C. for Secs. 12 & 13 only, (East)

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

A fir, 15" dia., bears N.28½°W., 27.3 ft., mkd. T20S  
R9W S12 CC BT.  
New BTs have a 2½"x¼" magnetic nail driven at the base on  
right side center and each corner established or remonumented  
has a magnet deposited in a white plastic case at the base of  
the stainless steel post. Aluminum angle irons were driven  
alongside each monument.