

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 318)

Set post 4" dia., 4 ft. long, with marked stone, 12" in ground for ¼ sec. cor., marked ¼ S on W. face; from which
Maple 20" dia., bears N.40°W., 20 lks. dist. mkd. ¼ S BT.
Maple 20" dia., bears N.72°E., 36 lks. dist. mkd. ¼ S BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12351)

The ¼ sec. cor. of sec. 7, determined at record bearing and distance from the original NW. bearing tree, and at record distance from a tree which does not agree with the record:

- A Cedar 36" dia., bears N.78°E., 36 lks. dist., marked with a healed blaze. (Rec. a Maple, bears N.72°E.)
- A Maple 32" dia., bears N.40°W., 20 lks. dist., marked with a healed blaze.

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: | ¼ S 7
1954

from which a new bearing tree:

- A Cedar 15" dia., bears S.51°E., 90 lks. mkd. ¼ S7 BT.

BLM dependent resurvey by Edith M Forkner, Cadastral Surveyor, under Group #2810, surveyed Sept. 2015/Jan. 2016 - (DCSO records Vol. 58 Page(s) 23451-2)

The ¼ sec. cor. of sec. 7 only, monumented with an iron post, 1" dia., firmly set, projecting 14" above ground, with a brass cap, oriented W., (properly) mkd.

from which the remains of the original bearing trees

- A cedar high stump, 40" dia., bears N.78°E., 23.8 ft., with no marks visible and a chewing tobacco can lid nailed to the stump at head height.
- A maple, 33" dia., bears N.40°W., 13.2 ft., with no marks visible on open decayed blaze.

and the remains of a bearing tree mkd. by Tillman, Bicknell, and Thielsen in 1953-54

- A decayed cedar stump, 18" dia., bears S.51°E., 59.4 ft., no marks visible.

continued next page

TOWNSHIP 20 RANGE 09 POINT IDENTIFIER # 700502

PRIMARY CORNER DESCRIPTION W. 1/4 cor. for Sec. 7 only, T20-8

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

and new bearing trees

An alder, 15" dia., bears N.45°E., 27.3 ft., mkd. ¼ S7 BT on bark.

A fir, 13" dia., bears S.56°E., 29.3 ft., mkd. ¼ S7 BT.

New BTs have a 2½"x¼" magnetic nail driven at the base on right side center and each corner established or remonumented has a magnet deposited in a white plastic case at the base of the stainless steel post. Aluminum angle irons were driven alongside each monument.