

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 6 only, T20-8

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by W. P. Wright, U.S. Deputy Surveyor, under Contract #486, dated August 1, 1883 (DCSO records Vol. 1 Page(s) 319)

-----  
Set post 4" dia., 4 ft. long, with marked stone 12" in ground for 1/4 sec. cor., marked 1/4 S on W. face; from which  
Fir 18" dia., bears S.19°E., 14 lks. dist., mkd. 1/4 S BT.  
Fir 12" dia., bears S.70°W., 36 lks. dist. mkd. 1/4 S BT.

GLO Resurvey by Thomas Tillman; Raymond Bicknell; Hans Thielsen; & Joseph Gawron, Cadastral Surveyors, under Group #305, Surveyed Aug. 1953/Sept. 1954 - (DCSO records Vol. 29 Page(s) 12353)

-----  
Point for the 1/4 sec. cor., at proportionate distance; there is no remaining evidence of the original corner.  
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap mkd: | 1/4 S 6  
1953  
from which  
A Hemlock 10" dia., bears N.76 1/2°E., 44 lks. mkd. 1/4 S6 BT.  
A Fir 43" dia., bears S.18 1/2°E., 12 lks., mkd. 1/4 S6 BT.

Tony Hostetter - For: Roseburg Resources - Jan. 2020 - C.S. File 65/105-7

-----  
Found - 1953 BLM brass cap, from which:  
22" Hemlock, 1953 BT, part of BT tag, bears; N.76 1/2°E., 29.0 ft to center.  
New BTs- 12" Fir, marked "X", BT tag, bears; S.68°W., 11.7 ft to spike.  
8" Fir, marked "X", BT tag, bears; N.21°W., 8.1 ft to spike.

Fd BC & 3 BTs 9/2020 by J Estabrook M177-40  
Lat & long per Garmin Etrex hand held GPS - NOT SURVEY GRADE  
N: 43°51'22.0 W: 123d42'12.8"