

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100240

PRIMARY CORNER DESCRIPTION 1/4 Cor. for Sec. 30; & 25 of T20-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, Deputy surveyor, under Contract #116, dated December 16, 1866 (DCSO records Vol. 1 Page(s) 87)

Set post for ¼ sec. corner; from which
A Chittewood 4" dia., bears S.68°W., 45 lks. dist.
A Chittewood 6" dia., bears N.85°E., 32 lks. dist.

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 106)

Set a post, 3 ft. long, 3" sq., 18" in the ground for ¼ sec. cor., marked ¼ S on W. face; and raised a mound of stone, 1½ ft. high and 2 ft. base alongside. Pits impracticable. The old cor. and its bearing trees have been burned; there is now only a thick growth of thimbleberries on this place.

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 248)

I made diligent search for the ¼ sec. cor. Failing to find any traces of it, I, therefore, Set a post, 4 ft. long, 4" sq., 24" in ground, for ¼ sec. cor. marked ¼ S on W. face; from which
A Fir 10" dia., bears S.72°30'E., 40 lks. dist. mkd. ¼ S BT.
A dead Fir 40" dia., bears N.20°30'W., 25 lks. dist. mkd. ¼ S BT.

Survey by Daniel Baker - For: U.S. Forest Service - June 10, 1986 - M 102-12

Set 2 3/8" x 30" alum. pipe, with 3" alum. cap mkd. "T20S R11W R10W 1/4 S25 S30 PLS 1978 1986".
New BTs -8" Fir N.28°E., 11.0 ft. scribed "¼ S30 BT"
9" Fir S.43½°W., 16.9 ft. scribed "¼ S25 BT"