

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19 & 30; & 24, 25, T20-11

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 106)

Set a post, 4½ ft. long, 4" sq., 24" in the ground, for cor. to secs. 30, 19, 24 and 25, marked T20S S19 on NE.; R10W S30 on SE.; R11W S25 on SW.; S24 on NW. faces, with 2 notches on S. and 4 notches on N. edges; from which

A Fir 40" dia., bears N.76°E., 14 lks. dist. mkd. T20S R10W S19 BT.

A Fir 12" dia., bears S.3°E., 105 lks. dist. mkd. T20S R10W S30 BT.

A Fir 7" dia., bears S.61½°W., 44 lks. dist. mkd. T20S R11W S25 BT.

A Fir 8" dia., bears N.2°W., 107 lks. dist. mkd. T20S R11W S24 BT.

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 249)

The cor. of secs. 24, 25, 19 and 30, which is a post, 2½ ft. above ground, firmly set in the ground, marked T20S Sec. 19 on NE.; R10W Sec. 30 on SE.; R11W Sec. 25 on SW.; Sec. 24 on NW. faces, with 2 notches on S. and 4 notches on N. edges; from which

A Fir 40" dia., bears N.76°E., 14 lks. dist. mkd. T20S R10W S19 BT.

A Fir 12" dia., bears S.3°E., 105 lks. dist. mkd. T20S R10W S30 BT.

A Fir 7" dia., bears S.61½°W., 44 lks. dist. mkd. T20S R11W S25 BT.

Fir 8" dia., bears N.2°W., 107 lks. dist. mkd. T20S R11W S24 BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - March 1968 - C.S. File 53/66-89

Found - Orig. 40" now 48" Fir, badly decayed stub, N.76°E., 9.2 ft., no scribe found.

Orig. 12" now 38" Fir, alive, S.3°E., 69.3 ft. old scar, opened previously, about 8" to false face.

Orig. 7" now 34" Fir, alive, S.61½°W., 29.0 ft. opened and find "T20" scribe and reverse under 70+ rings.

Orig. 8" now 40" Fir, alive, N.2°W., 70.6 ft. We do not open.

(Cont. Next Page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100300

PRIMARY CORNER DESCRIPTION Sec. Cor. for 19, 30; & 24, 25, T20-11

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Set Brass cap at cor. mkd:

County Surveyors Office

R	T 20 S	R
11	S 24 S 19	10
W	S 25 S 30	W

1968

New BTs -7" D.Fir S.83°W., 21.7 ft. mkd. T20S R11W S25 CSBT

12" D.Fir N.29°W., 27.8 ft. mkd. T20S R11W S24 CSBT

14" Maple N.4°E., 24.6 ft. mkd. T20S R10W S19 CSBT

14" Maple S.62°E., 26.5 ft. mkd. T20S R10W S30 CSBT

Corner lies 30 ft. East of spur, sloping North.

Fd. OK, June 1986 by D. Baker - M 102-12