

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100340

PRIMARY CORNER DESCRIPTION W. 1/4 Cor. for Sec. 19 only

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 107)

A Maple 10" dia., which I marked $\frac{1}{4}$ S on W. side, for $\frac{1}{4}$ sec. cor.; from which

A Maple 24" dia., bears S.80°E., 3 lks. dist. mkd. $\frac{1}{4}$ S BT.

A Maple 5" dia., bears N.23°W., 4 lks. dist. mkd. $\frac{1}{4}$ S BT.

Cor. Fd. by Nathaniel Martin, GLO Surveyor, under Contract #599, dated June 20, 1892 (DCSO Records, Vol. 1 page 249)

Survey by Michael J. Schwartz and L.W. Hunnemuller - For: U.S. Forest Service - Oct. 1985 - M 99-79 A-B

Set a 3½" x 30" alum. flared pipe with alum. cap, stamped: "T20S R11W R10W 1/4 S19 1984 PLS 1922"., from which

7" D.Fir bears S.10°E., 2.4 ft. scribed " $\frac{1}{4}$ S19 BT"

10" D.Fir bears N.38°E., 21.2 ft. scribed " $\frac{1}{4}$ S19 BT"