

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only, T20-11

Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____
 Alias _____ Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 107)

 A Chittem tree, 6" dia., which I marked for cor. to secs. 19, 18, 24 and 13, T20S S18 on NE.; R10W S19 on SE.; R11W S24 on SW.; S13 on NW. sides, with 3 notches on N. and S. sides; from which

- A Cherry 6" dia., bears N.40½°E., 34 lks. dist. mkd. T20S R10W S18 BT.
- A Fir 6" dia., bears S.5½°E., 25 lks. dist. mkd. T20S R10W S19 BT.
- A Fir 36" dia., bears S.81°W., 15 lks. dist. mkd. T20S R11W S24 BT.
- A Fir 15" dia., bears N.74°W., 13 lks. dist. mkd. T20S R11W S13 BT.

Cor. Fd. and used in GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 244) AND on Page 250:

"I destroyed all marks on this cor. relating to R10W."

Douglas Co. Surveyors Office - Vernon "Ray" Tracy, Jack Heritage, V. Perron, crew - March/April 1968 - C.S. File 53/66-62

 Found - Unrecorded 1¼" I.Pipe at corner point.
 Orig. 36" now 48" Fir, alive, S.81°W., 9.9 ft., shows bark scribe in poor condition. Rescribe "T20S R11W S24 CS BT"
 Orig. 15" now 30" Fir, N.74°W., 8.6 ft., alive, shows good scar. Do not open.

No trace of orig. corner tree, nor other BTs.
 Set Brass cap at cor. mkd: County Surveyors Office

	T	20	S
R	S	13	R
11W	S	24	10W
		1968	

Reset Iron pipe alongside.
 New BT - 15" Cedar N.56°W., 15.6 ft. mkd. T20S R11W S13 CS BT
 Corner lies on steep E. slope about 100 ft. above creek, course N. and 99.3 ft. N.3½°E., of C.C. to Secs. 18 & 19, T20-10.

Survey by P. Fox, Engineer #3282 - For: U.S. Forest Service Setp. 28, 1977 - C.S. File 60/11

 Found - 1968 DCSO brass cap in mound of rock on steep rocky hillside. (Cont. Next Page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100402

PRIMARY CORNER DESCRIPTION Sec Cor for 13 & 24 only, T20-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

48" Fir stump with tag bears S.81°W., 9.9 ft.
30" Fir stump with tag bears N.74°W., 8.6 ft.
15" Cedar stump with tag bears N.50°W., 16.6 ft.
Drilled hole in rock ledge to receive the iron pipe and a
recess was made for the brass cap and then cemented in place.
No new accessories.

Fd. OK, April 1987 by R. Hintz - M 104-9