

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100444

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 13 only, T20-11

Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_  
Alias \_\_\_\_\_ Description \_\_\_\_\_

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 108)

-----  
Set a post, 3 ft. long, 3" sq., 18" in the ground, for ¼ sec. cor. mkd. ¼ S on W. face; from which

A Fir 12" dia., bears S.12°W., 93 lks. dist. mkd. ¼ S BT.

A Fir 24" dia., bears N.20°E., 35 lks. dist. mkd. ¼ S BT.

-----  
Cor. Fd. by Cadastral Surveyor, Nathaniel Martin, June 1892, (DCSO records, Vol. 1 Page 250)

-----  
James W. Prochnau - For: USFS - Oct. 12, 1971 (added 7/10/2017) - M 43-56

-----  
Found - no monument fd.

Orig. BT tagged by USFS - now windfall.

-----  
Survey by Michael J. Schwartz and L.W. Hunnemuller - For: U.S. Forest Service - Oct. 1985 - M 99-79 A&B

-----  
Set an alum. survey cap on a 5/8" iron rod in rock, stamped "T20S R11W R10W 1/4 S13 1985 RLS 1922", from which

A 32" D.Fir bears N.39°E., 16.1 ft. scribed "¼ S18 BT"

A 12" Maple bears S.61°E., 68.3 ft. scribed "X BT"