

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100600

PRIMARY CORNER DESCRIPTION C C for Secs. 6 & 7 only, (West)

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under Contract 599, dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 252)

At point of intersection
Set a stone, 10x8x8, 7" in ground for closing corner to secs. 6 & 7, marked with C C and 5 notches on S. and 1 notch on N. faces and raised mound of stone, 30" high and 24" base alongside. Pits impracticable.

Survey by James W. Prochnau - For: U.S. Forest Service - May 1971 (Revised Aug. 1971) - C.S. File 55/201-8; M 41-77 (Revised on M 43-56 -Corner #14 on map)

No evidence of original corner found.
At the properly proportioned position I placed a 2" x 36" galv. I.P. flanged at the bottom and capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth. I stamped the disk:

	T20S	CC
S12	S 6	R10W
	S 7	
	1971	
	4185	

I established new BTs as follows. Each tree has a scribed face and a U.S.F.S. BT sign breast high and facing the monument.
A 16" Fir bears N.60°E., 72.25 ft.
An 18" Fir bears S.49°E., 47.59 ft.

Survey by Donald Peel - For: Davidson Industries, Inc. - May 6, 1983 - C.S. File 58/274 and M 94-64 (Amended, See C.S. File 62/19 and M 97-64)

Found - 10" x 7" x 7" stone mkd. C C with 1 notch in circle of stones approx. 4 ft. in diam.
Set U.S.F.S. alum. monument in mound of stone, from which
34" Fir, N.79½°E., 92.5 ft.
20" Alder S.45½°E., 12.0 ft., bark scribed.
17" Fir N.60°E., 95.8 ft., Prochnau BT.
20" Fir snag S.72°E., 56.6 ft., Prochnau BT.
Closing corner set by J. Prochnau in 1971 bears N.51°33'26"E., 23.58 ft.

Found stone removed, Sept. 18, 1984 - DCSO - C.S. 62/21-2