

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100642

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only, T20-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by Wm. Thiel, Deputy Surveyor, under Contract #567, dated Feb. 16, 1891 (DCSO records Vol. 1 Page(s) 110)

Set a sandstone, 12x8x7 ins., 8" in the ground, for ¼ sec. cor., marked ¼ on W. face; from which

A Fir 6" dia., bears S.11°E., 90 lks. dist. mkd. ¼ S BT.

A Fir 5" dia., bears N.87°W., 75 lks. dist. mkd. ¼ S BT.

Cor. Fd. and used in GLO survey by Nathaniel Martin, June 1892 - (DCSO Records, Vol. 1 Page 253)

Survey by James W. Prochnau - For: U.S. Forest Service - May 1971 - M 41-77 (Revised Aug. 1971, C.S. File 55/201-15; M 43-56 - (Corner #11 on Map))

No evidence of original corner found.

At the properly proportioned position, I placed a 2" x 36" galv. I.P. flanged at the bottom and capped with a bronze disk welded on top. Monument projects 6" above ground. I filled in around the pipe monument with stone and packed earth. I stamped the disk:

¼ S1 |
1971 |
4185

I established new BTs as follows. Each BT has a scribed face and a U.S.F.S. BT sign breast high and facing the monument.

A 16" Fir bears N.82°W., 31.00 ft.

An 18" Fir bears N.57°W., 42.18 ft.

Survey by Ernesto R. Alvarado, USFS Deputy - DCSO - Witness: Jill O'Neil - April 17, 1978 - C.S. File 59/46-82

Found - 2½" brass cap in good condition, 4" below the surface of road, mkd. T20S R11W S1 only 4185.

Uprooted D.Fir stump bears N.84°W., 33.10 ft.

22" D.Fir bears N.52°W., 43.04 ft. scribe marks visible.

New BT - 18" D.Fir bears S.70°W., 31.32 ft. double faced scribed "¼ S1" upper blaze and "CS BT" lower blaze.

Go South on USFS Road #1909 about 3.6 miles to the Siuslaw National Forest boundary sign on the left side of the road. The corner lies in the center of the road.

Survey by Donald Peel - For: Davidson Industries, Inc. - May 6, 1983 - C.S. File 58/274; M 94-64 (Amended C.S. File 62/19; M 97-64)

Set U.S.F.S. alum. monument buried 4" below surface of Road No. 4811, from which (Cont. Next Page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 100642

PRIMARY CORNER DESCRIPTION E. 1/4 Cor. for Sec. 1 only, T20-11

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

23" Fir N.42°W., 52.7 ft., Prochnau BT.
18" Fir N.88°W., 32.2 ft., Prochnau BT.
1/4 Corner set by J. Prochnau in 1971 bears N.13°36'00"W.,
11.77 ft.