

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 140200

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 30 & 31

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 180)

Set ¼ sec. post; from which
 A Hemlock, 10" dia., bears N.14°W., 15 lks.
 A Hemlock, 8" dia., bears S.15°E., 27 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 254)

Clifford A. Stephens - for: Coos Head Timber Co. - Filed April 1958 - C.S. File 42/362 - M 10-3

By proportion, I set the ¼ corner 2618.88 ft. West of the NE corner of sec. 31. The West ½ of the section receiving 2646.20 ft. to close in on the Range line.
For the ¼ corner I set ½" iron pipe & post from which:
 A Cedar, 8" dia., bears N.13°W., 14.0 ft.
 A Fir, 12" dia., bears S.34°W., 12.0 ft.

Fd. Ok by Richard Hintz Sept. 1985, M 99-51

Daniel Baker, PLS 1978 - for: USFS - June 1986 - M 102-12

Set - 2 3/8" x 30" alum. pipe with 3" alum. cap.
 16" Cedar S.2¼°W., 18.1 ft. scribed "¼ S30 BT"
 16" Cedar, N.87½°W., 26.5 ft. scribed "¼ S31 BT"
 2 3/8" x 30" alum. pipe with 3" alum. cap as a reference point bears S.89°25'40"W., 37.38 ft.
Note- ½" iron pipe (M 10-3) bears S.88°25'40"W., 98.2 ft. (1958)

Fd. ok by R. Stuntzner, 2/1992, M 114-80
Fd. ok by Royce Hill 7/1992, M 115-71