

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 140300

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 19 & 30

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.B. Byars under contract #202, dated March 11, 1874 - (DCSO records Vol. 1 Page(s) 188)

Set a chitterwood post, 40" long, 5" dia., 18" in ground, for 1/4 sec. cor; from which

A Fir 20, 52" dia., bears N.52°W., 29 lks.

A Chitterwood, 4" dia., bears S.50°E., 30 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol 1 Page(s) 242)

Richard Hintz - For: International Paper Co. - April 1983 - M90-42

Found - 3/4" IP

60" Fir windfall is lying approx. 35 ft. south of hole and/or depression in ground. hole bears N.52°W., 19 ft. from IP.

See USFS index file No. R-3 at Mapleton.

Set - Replace the 3/4" IP with 1 1/4" IP/BC.

10 Fir bears S.48°30'E., 30.3 ft., scribed.

20" Cedar bears N.60°W., 45.0 ft., scribed.

Daniel Baker, LS 1978 - For: USFS - June 10, 1986 - M 102-12

Found - 1 1/2" iron pipe with brass cap.

14" Fir, S.48 1/4°E., 30.3 ft. (closed face)

22" Cedar, N.61°W., 46.1 ft. (closed face)

Set - 2 3/8" x 30" alum. pipe with 3" alum. cap as a reference point bears S.0°16'53"W., 35.75 ft. Cap stamped "T20S R10W 1/4 S19 S30 PLS 1978 1986 35.75 N.0°16'53"E."