TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 140400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 18 & 19

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 244)

Marked a Cherry tree, 6" dia., for ¼ sec. cor., mkd: ¼ S on N face; from which
A Maple, 12" dia., bears N.45°E., 40 lks., mkd: ¼ S BT.
A Maple, 10" dia., bears S.60°E., 25 lks., mkd: ¼ S BT.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April 1968 - C.S. File 53/66-65

Found - Orig. 12" now 26" Maple, alive, N.45°E., 26.4 ft., open & shows scribe on badly decayed blaze. Rescribe: "¼ S18 CS BT"

Set - Brass cap at cor. mkd: COUNTY SURVEYOR'S OFFICE 1968 ¼ S 18 / S 19
30" Maple S.10°E., 11.9 ft., mkd: "¼ S19 CS BT"

Note - No trace of corner tree or other OBTs. This corner lies on SW slope about 150 ft. East of Johnson Creek.

Michael J. Schwartz, LS 1922 & L.W. Hunnemuller, LS 1050, - Sulphur Cadastral Survey, Siuslaw Nat'l. Forest, USFS - Oct. 1985 - M 99-79 A&B

Found - Douglas Co. brass cap, properly mkd.
28" Maple, bears N.45°E., 27.3 ft. with open face, (rec. N.45°E., 26.4 ft. 1892)
30" Maple stub, bears S.10°E., 11.9 ft. with healed scar.

New BT - 22" double Alder, bears N.83°W., 38.4 ft., scribed "¼ S18 BT"
No suitable bearing trees to south.