

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 6 & 7

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 247)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which

A Maple, 4" dia., bears N.40°E., 75 lks., mkd: ¼ S BT.

A Maple, 5" dia., bears S.66°E., 80 lks., mkd: ¼ S BT.

James W. Prochnau - For: USFS - May & Oct., 1971 - M 43-56 & C.S. File 55/201-7 - (Corner #21 on Map)

No evidence of orig. corner found.

At the properly proportioned position I placed a 2"x36" galv. IP, flanged at the bottom & capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone & packed earth. I stamped the disk:

¼ $\frac{S\ 6}{S\ 7}$

1971

4185

I established new BTs as follows. Each tree has a scribed face & a USFS BT sign breast high & facing the monument, mkd:

A 18" Fir stump bears N.72°E., 28.23 ft.

A 26" Fir stump bears S.52°E., 13.4 ft.

Michael J. Schwartz, LS 1922 & L. W. Hunnemuller, LS 1050, - Sulphur Cadastral Survey, Siuslaw Nat'l. Forest, USFS - Oct. 1985 - M 99-79 A&B

Found - Brass cap set by Prochnau in 1971
18" Fir stump, bears N.72°E., 28.23 ft.
26" Fir stump, bears S.2°E., 13.4 ft.

Set - A 3½"x30" alum. flared pipe with alum. cap stamped:
T20S R10W ¼ S6 S7 1984 RPLS 1922. (Cap lies
S.69°51'20"E., 7.99 ft. from Prochnau's corner.)

New BTs- A 5" D.Fir, bears S.28°E., 14.8 ft. scribed "X" BT.

New BO - A 3½"x30" alum. flared pipe with alum. cap stamped:
T20S R10W ¼ S6 RM S12-39W., 44.7 ft. 1984 RPLS
1922.