

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 180)

-----  
Set post for corner to secs. 19, 20, 29, & 30  
A Hemlock, 24" dia., bears N.35°E., 38 lks.  
A Hemlock, 12" dia., bears S.50°E., 57 lks.  
A Hemlock, 10" dia., bears S.42°W., 9 lks.  
A Fir, 30" dia., bears N.30°W., 38 lks.

Roy Gibson - June 1957 - C.S. File 42/275

-----  
No trace of orig. corner was found, corner set by double proportionate measurement.

Set a 4x4 post at point for corner, from which:

- 32" Fir bears N.15°W., 19.5 ft.
- 16" Hemlock bears N.64°E., 15.5 ft.
- 24" Fir bears S.82°E., 24.0 ft.
- 34" Fir bears S.59°W., 41.5 ft.

Richard J. Hintz, PLS #497 - For: International Paper Co. - April 1983 - M 90-42

-----  
Found - 4x4 post & 4 BT stumps per 1957 ren.  
Set - Replaced post with 1¼" x 36" iron pipe with brass cap mkd: PLS 497

Richard J. Hintz, PLS #497 - For: Siuslaw National Forest - April 1987 - M 104-9

-----  
Found - 1¼" IP stamped brass cap (PLS 497-1983) from which:  
27" Hemlock stump bears N.61°05'E., 15.1 ft. to a ½"x30" IR set in the top center (visible scribe on partially healed blaze)  
24" Fir stump bears S.82°05'E., 24.1 ft. to a ½"x30" IR set in the top center (healed blaze)  
42" Fir stump bears S.61°10'W., 42.5 ft. to a ½"x30" IR set in the top center (no visible scribe on rotted blaze)  
37" Fir stump bears N.15°27'W., 20.6 ft. to a ½"x30" IR set in the top center (visible scribe on rotted blaze)

No previous record of iron rods in center of stumps.

continued next page

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 200300

PRIMARY CORNER DESCRIPTION Cor. Secs. 19, 20, 29, & 30

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Jerry Estabrook - For: Menasha Forest Products Corp. - June 2014 - M168-20

Found - 1¼" iron pipe with 2½" brass cap marked T20S R10W S19 S20 S29 S30 PLS497 1981".

A 27" Hemlock stump with ½" iron rod in center and tags bears N.61°E., 15.1'.

A 24" Fir stump with ½" iron rod in center and tag bears S.82°E., 25.1' RECORD 24.1'.

A 42" Fir stump with ½" iron rod in center bears S.61°W. 42.5'.

A 37" Fir stump with ½" iron rod in center bears N.15°W., 20.6'.

NEW BTs- A 19" Hemlock face scribed "SW S20 BT" with x-chop and tag bears N.55°E., 24.4' to a spike at side center.

A 14" Hemlock face scribed "NW S29 BT" with x-chop and tag bears S.37°E., 6.9' to a spike at side center.

Lat. and Long. per Garmen Etrex hand held GPS

N: 43°48'39.3" W: 123°55'36.3"