

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by W.B. Byars under contract #202, dated March 11, 1874 - (DCSO records Vol. 1 Page(s) 189-90)

Set Fir post, 42" long, 5" dia., 18" in ground, for corner to secs. 7, 8, 17, & 18; from which
 A Fir, 6" dia., bears N.62°E., 17 lks.
 An Alder, 9" dia., bears S.10°E., 48 lks.
 A Fir, 5" dia., bears S.40°W., 76 lks.
 An Alder, 5" dia., bears N.35°W., 19 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 245)

Wilford N. Haines - For: USFS, US Plywood, & International Paper - Nov. 1965 - M 31-6

Found - 5" Fir S.40°W., 76 lks., now stub about 2 ft. high, scribed "W" BT plain.
Set - 1" x 1" x 36" T-iron.
 There is 2 unrecorded BTs, both Firs, these scribed trees here in 1941 when I first visited this corner.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April 1968 - C.S. File 53/66-83

Found - Haines' "T" Iron set a corner from one orig. BT. Orig. 5" Fir, now badly decayed stump with "WBT" scribe S.40°W., 50.2 ft.
Unrecorded BTs as follows:
 20" D.Fir snag S.35°W., 54.0 ft., bark scribed: "T20S R10W S17"
 23" D.Fir snag S.73°W., 46.3 ft., bark scribed: "S7 T20S R10W"
Set - Brass cap at cor. mkd: COUNTY SURVEYOR'S T20S R10W (reset "T" iron OFFICE 1968 S 7|S 8 alongside) S 18|S 17
 26" Maple N.81°E., 7.0 ft. mkd: T20S R10W S8 CS BT.
 24" Maple S.22°E., 57.7 ft. mkd: T20S R10W S17 CS BT
 No other suitable trees available.
This corner lies on steep easterly slope approx. 50 ft. w. of small ravine.

James W. Prochnau - For: USFS - Oct. 12, 1971 (added 7/10/2017)- M 43-56

Found - Bronze cap
 Orig. 5" Fir now stub, S.40°W., 50.2 ft.
New - 20" Maple bears S.79½°W., 10.0 ft.

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 200500

PRIMARY CORNER DESCRIPTION Cor. Secs. 7, 8, 17, & 18

Alias	Description
_____	_____
_____	_____
_____	_____
_____	_____

Fd. by Richard Hintz 4/1983 - M 90-42

Michael J. Schwartz, LS 1922 & L. W. Hunnemuller, LS 1050, - Sulphur Cadastral Survey, Siuslaw Nat'l. Forest, USFS - Oct. 1985 - M 99-79 A&B

Found - DCSO brass cap properly marked.
 18" Maple, bears S.22°E., 56.0 ft. with healed face.
 (Rec. 24" Maple 57.7 ft. 1968)
 Decayed Fir, bears S.40°W., 50.2 ft. with a pitch
 slab, scribed W BT (1874)
 20" D.Fir stump, bears S.40°W., 55.3 ft., with bark
 scribing visible: "T20S R10W S17"
 25" D.Fir snag (12 ft.) bears S.76°W., 44.7 ft. with
 bark scribing visible. (1968)
 29" Maple, bears N.81°E., 7.0 ft., with a severe
 lean & scars visible. (1968)

New BOs- Marked a concrete nail in large sandstone boulder,
 N.63°W., 10.7 ft.
 Set a 3½" x 30" alum. flared pipe, with alum. cap,
 for reference monument, stamped: T20S R10W RM S18
 N1-14E 49.3 1985 RLS 1922.