TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 200540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 7 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 271 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 198)

Set post for ¼ sec. cor; from which
A Maple, 5" dia., bears S.32°W., 18 lks.
A Maple, 7" dia., bears S.70½°E., 49 lks.

James W. Prochnau - For: USFS - May 1971 - C.S. File 55/201-13 & M 43-56 - (Corner #3 on Map)

No evidence of orig. corner found.
At the properly proportioned position I placed a 2" x 36 galv. IP flanged at the bottom & capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone & packed earth.
I stamped the disk: ¼
S 7|S 8
1971
4185
I established new BTs as follows, each BT has a scribed face and a USFS BT sign breast high & facing the monument.
A 10" Spruce bears S.69°E., 26.6 ft.
A 10" Maple bears S.30°W., 59.43 ft.

Fd. Ok by Richard Hintz, April 1983 - M 90-42

Michael J. Schwartz, LS 1922 & L. W. Hunnemuller, LS 1050, - Sulphur Cadastral Survey, Siuslaw Nat'l. Forest, USFS - Oct. 1985 - M 99-79 A&B

Found - 1971 brass cap, mkd: ¼ S7 S8 1971 4185.
18" D.Fir bears (S.69°E., 26.6 ft. 1971) tree so badly "J"d, couldn't tell where to measure to.
11" Maple, S.30°W., 58.4 ft. scribing visible. (Rec. 59.43 ft. 1971)
New BT - 10" D.Fir, bears S.43°E., 44.6 ft. scribed: ¼ S8 BT.