

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 200640

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 5 & 6

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by F. M. Johnson, under contract #303 dated Sept. 30, 1878 - (DCSO records Vol. 1 Page(s) 200)</p> <p>-----</p> <p>For post a Maple tree, 12" dia., from which A Maple tree, 6" dia., bears N.78°E., 33 lks. No other tree convenient to the line.</p>
<p>Fd. &amp; used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 242)</p>
<p>Douglas Co. Surveyors Office - H.L. Eppstein, County Surveyor - J. Feurgeson - F. Koepke - B. Lane - July 17, 1929 - "Old" Corner Renewal Book Vol. 1 Pg. 7 (&amp; C.S. 13/40 pg 13/14)</p> <p>-----</p> <p>Set - 4" x 36" Fir limb for corner from Maple witness tree. 18" Maple, N.2°W., 8 ft. 28" Fir, S.13°E., 25 ft.</p>
<p>James W. Prochnau - For: USFS - Oct. 12, 1971 - M 43-56 &amp; C.S. File 55/201-5 (Corner #5 on map)</p> <p>-----</p> <p>No evidence of orig. corner found. At the properly proportioned position I placed a 2" x 36" galv. IP flanged at the bottom &amp; capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone &amp; packed earth. I stamped the disk:</p> <p style="text-align: center;">¼ S 6 S 5 1971 4185</p> <p>I established new BTs as follows. Each BT has a scribed face &amp; a USFS BT sign breast high &amp; facing the monument, mkd: A 28" Maple bears N.15°E., 30 ft. A 32" Hemlock (possible Sitka Spruce per Dick Hanslin, 4/17/1979) bears N.44°W., 80.86 ft.</p>
<p>James W. Prochnau - For: Siuslaw National Forest - M 104-51 A&amp;B - June 30, 1987</p> <p>-----</p> <p>Set - USFS 2½" x 30" alum. pipe with ¾" alum. cap stamped "T20S R10W ¼ S6 S5 1987 PLS 1305" 16" Maple bears N.7¼°E., 64.0 ft., scribed "¼ S5 1987" USFS 2½" x 30" alum. pipe with ¾" alum. cap stamped "RM ¼ S5 1987 PLS 1305" bears N.2°25'E., 313.0 ft. USFS ½" x 30" alum. pipe with ¾" alum. cap stamped "RM ¼ S5 1987 PLS 1305" bears S.9°45'W., 90.3 ft.</p>