

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by W.B. Byars under contract #202, dated March 11, 1874 - (DCSO records Vol. Page(s) 189)

-----

Set Chittenwood post, 40" long, 5" dia., 20" in ground, for 1/4 sec. cor.; from which

A Maple, 8" dia., bears N.70°E., 24 lks.

A Maple, 40" dia., bears S.40°W., 15 lks.

Fd. & used on GLO survey by William Thiel under contract 271 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 194)

Douglas Co. Surveyors Office - Arthur Boyer, Douglas Co. Surveyor - John Wroe & Henry Wroe witnesses - Dec. 12, 1939 - C.S. File 16/58 & "Old" Corners Renewed Vol. 1 Pg. 7

-----

Set 3/4" pipe for corner on true line & midway between the sec. corner 1/2 mile to East & West, from which:

A Fir 36" dia., bears N.83 1/2°E., 261.5 ft. on bank of N. Fork Smith River, barked blazed & scribed: 1/4 S17 T20S R10W CS BT.

An Alder, 24" dia., bears S.32°W., 100.5 ft., mkd: 1/4 S20 T20S R10W CS BT

About 54' N of this corner there is a 3/4" pipe set at a point that looks like the orig. corner from which the stump of a 12"± Maple bears N.70°E., 16 ft. & the snag 4' high of a 50"± Maple bears S.40°W., 10 ft. In 1874 Byars ran the W 1/2 of the line between 17 & 20 & set the 1/4 cor. between 17 & 20 without running the full mile, about 4 years latter Thiel continued running 1/2 mile East from Byars corner. This corner above look like the corner. The 50" Maple shows the round for the blaze but was burned out inside the blaze, from this corner is a 3/4" IP the above BT shows as follows:

36" Fir S.81°E., 175 ft.

24" Alder S.46°W., 198 ft.

See BLM letter dated 2/7/1940, from Joseph Gonong, District Cadastral Engineer and notation of opinion by District Attorney, in file (C.S. File 16/58) concerning the 2 fd. Maple stumps being the true corner.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - April 1968 - C.S. File 53/66-66

-----

Found - BTs as recorded in 1939.

36", now 48" Fir, alive, S.81°E., 175.0 ft., scribed "1/4 S17 T20S R10W CS BT"

No trace of any corner pipes or other BTs.

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 240400

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 17 & 20

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

At orig. cor. point, see letters by Boyer & Ganong, Feb. 1940, C.S. File 16/58.  
Set - Brass cap at cor. mkd: COUNTY SURVEYOR'S T20S R10W  
(Set 6 ft. steel fence OFFICE 1968 S 17  
post alongside BC)  $\frac{1}{4}$  S 20  
9" Ash N.30°E., 354.0 ft. mkd: " $\frac{1}{4}$  S17 CS BT"  
No other trees available on West side of river.  
Note- Boyer's BT is on east side of river. Also point of  
Boyer's proportioned  $\frac{1}{4}$  corner bears S.57°W., 103.3  
ft. Corner falls in E. G. Dunn's field approx. 90  
ft. West of N. Fork of Smith River.

Fd. by Richard Hintz, April 1983, M 90-42  
Fd. by Bruce Shaner, 4/1/1993, 1993-0072 A & B