TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 240600

PRIMARY CORNER DESCRIPTION Cor. Secs. 5 & 8

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 270 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 198-9)

Set ¼ sec. post; from which
An Alder, 4" dia., bears N.34°E., 33 lks.
An Alder, 8" dia., bears S.16°E., 43 lks.

James W. Prochnau - For: USFS - May & Oct., 1971 - M 43-56 & C.S. File 55/201-2 (Corner #22 on map)

No evidence of orig. corner found.
At the properly proportioned position I placed a 2" x 36" galv. IP flanged at the bottom and capped with a bronze disk welded on top. The monument projects 6" above ground. I filled in around the pipe monument with stone & packed earth.
I stamped the disk:

¼ S 5
S 8
1971
4185

I established new BTs as follows. Each BT has a scribed face and a USFS BT sign breast high & facing the monument, mkd:
A 6" Fir bears N.36°E., 90.7 ft.
A 12" Fir bears S.78°W., 92.5 ft.

Fd. ok by Richard Hintz, April 1983 - M 90-42

James W. Prochnau - For: Siuslaw National Forest - M 104-51 A&B - June 30, 1987

Found - A 2½" brass cap on a 2½" galvanized iron pipe set by Prochnau in 1971.
24" D.Fir bears S.78°W., 92.5 ft., healed.
15" D.Fir bears N.36°W., 90.7 ft., healed.
Set - **A 8" D.Fir corner tree replaces** the brass cap on pipe, tree mkd: "SC ¼ S5" on North side of tree.
The found 2½" brass cap on a 2½" galv. iron pipe has been modified and used as a RM, bearing: S.25°23'W., 10.8 ft. mkd: "RM ¼ S8"
Note - I remove tags & signs from 1971 BTs.