

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

<p>GLO survey by John W. Meldrum, under contract No. 116 dated Dec. 12, 1867 - (DCSO records Vol. 1 Page(s) 178)</p> <p>-----</p> <p>Set stone, 20x10x8 for corner to secs. 28, 29, 32, & 33; from which An Alder, 20" dia., bears N.82°W., 34 lks.</p>				
<p>Roy Gibson - June 1957 - C.S. File 42/275</p> <p>-----</p> <p>No trace of orig. cor. was found. Corner set by double proportional measurement. At corner point made an X on East face of 4 ft. sandstone outcrop, from which 38" Fir, bears N.45½°W., 35.8 ft. 14" Maple, bears N.88°E., 48.6 ft. 6" Fir, bears S.21°W., 4.2 ft.</p>				
<p>Tom O. McCullough - For: USFS - April 1970 - C.S. 55/148-6</p> <p>-----</p> <p>Corner established in 1878, re-established by Gibson in June 1957, by double proportional measurements. Found - An "X" 8" high on East face of 4' sandstone outcrop, scribed by Gibson in 1957, from which 44" Fir bears N.45½°W. 35.8' visible scribing, w/tag 14" Maple bears N.88°E. 48.6' scribing visible w/tag 6" Fir bears S.21°W., 4.2', face healed, w/tag, windthrown.</p> <p>Set - 2"x30" iron pipe with brass cap mkd: T20S R10W WC 4.4 ft. East of true corner WC <table border="1"><tr><td>S 29</td><td>S 28</td></tr><tr><td>S 32</td><td>S 33</td></tr></table> 1970 650</p> <p>11" Fir bears N.32°W., 23.2 ft. scribed S29 BT. 11" Fir bears S.89½°W., 16.1 ft. scribed S32 BT.</p>	S 29	S 28	S 32	S 33
S 29	S 28			
S 32	S 33			
<p>Jerry Estabrook - For: Rayonier- Aug. 2018 - M174-60</p> <p>-----</p> <p>Found - An X marked in east face of sand stone outcrop, per CS42/275. Found witness corner monument - A 2" IP with 2" brass cap (properly) marked bears N.79°E., 4.49' record east 4.4' from X mark to witness corner.</p> <p>BTs for section corner - A 6" fir wind fall, with tag bears S.21°W., 4.2'. A 26" fir, with healed face, tag and new X-chop bears N.25°W., 25.4'. This was originally a BT For the witness corner but has shifted down hill from its original position. continued next pg</p>				

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 300200

PRIMARY CORNER DESCRIPTION Corner Secs. 28, 29, 32, & 33

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Found BO for section corner -
 A steel fence post with sign bears S.70°E., 3.8'.
New BT marked for section corner -
 A 19" Fir, face scribed "NE S32 BT" with X-chop and
 tag bears S.44°W., 10.3' to a spike at side
 center.
Found BTs for witness corner -
 A rotten fir wind fall with tag bears S.89°30'W.,
 16.1'.
 A 26" Fir healed face, tag and new X-chop bears
 N.34°W., 26.8', record N.32°W., 23.2'.
Lat. and Long. per GARMIN ETREX hand held GPS
 N: 43°47'47.5" W:123°54'26.3"