

PRIMARY CORNER DESCRIPTION Cor. Secs. 20, 21, 28, & 29

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by William Thiel under contract 271 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 195)

An Alder, 8" in dia., is post for corner of secs. 20, 21, 28, & 29 from which

- An Alder, 5" dia., bears S.35½°E., 54 lks.
- An Alder, 6" dia., bears S.39½°W., 59 lks.
- An Alder, 8" dia., bears N.79½°W., 51 lks.
- A Fir, 12" dia., bears N.33½°E., 75 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO rec. Vol. 1 Page(s) 231-2)

Roy C. Gibson - June 1957 - C.S. File 42/275

Found - Orig. BT, bears N.34°E., 75 lks.
Set - Post at corner, from which

- 20" Alder bears S.36°W., 35.4 ft.
- 14" Alder bears N.34°W., 27.4 ft.
- 42" Fir bears N.35°E., 46.4 ft.
- 12" Maple bears S.82°E., 11.7 ft.

Douglas Co. Surveyors Office - Vernon "Ray" Tracy & Crew - May 1968 - C.S. File 53/66-119

Found - Unrecorded 3/4" IP at corner & BTs as follows:

- 46" Fir, N.35°E., 46.4 ft. (1957). Bark scribed "BT S21" previously opened to old injury about 50 years ring growth - no scribe - we opened an additional 40 rings no burl - face or orig. scribe fd. I do not believe this is orig. BT.
- 20" Alder S.36°W., 36.4 ft scribed "BT S 2" on unhealed blaze, tree hollow, appears to be too young for orig BT

We do not find any other BTs - also old stump in front of Fir to NE that must have been alive at time orig. corner was set.

Note - The Fir to NE that was apparently used as the orig. BT by Mr. Gibson in 1957 may have been accepted from the scar alone - we opened approx. 90 - 100 years of ring growth & failed to find scribe or burl wood. The scar at a glance appears to be axed, but I feel after close inspection that is an injury rather than an axe blaze. It is possible that Gibson fd. something not visible now - in view of the lack of evidence at this time & because there is an IP set - we do not set brass cap or mark new BTs. Signed V. R. Tracy

cont.

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Tom O. McCullough - For: USFS - April 1970 - C.S. 55/148-7

 Found - 3/4" IP set by Gibson in 1957, from which:
 Orig. 48" Fir bears N.35°E., 46.4 ft. scribing visible, with tag, has been chopped out.
 20" Alder bears S.36°W., 35.4 ft. scribing visible, with tag, has been chopped out.
 Set - 2" x 30" IP with brass cap mkd: T20S R10W

20	21
29	28

650 1970
 from which
 12" Maple bears N.68°W., 26.2', scribed S20 BT w/tag
 12" Hemlock bears S.1°E., 54.5' scribed S28 BT w/tag
 2 fence posts with signs: ± 5 ft. W. facing S & 5 ft. S facing W.

Jerry Estabrook - For: Menasha Log Co. LLC The Campbell Group, LLC ITS Manager - 3/2012 - M163-41

 Found - 2" iron pipe with brass cap marked "T20S R10W 20 21 28 29 1970 650" per CS 55/148.
 A 48" fir stump with no visible marks brs. N.35°E., 46.4'.
 A rotten hemlock stump with no visible marks brs. S.01°E., 54.5'.
 A 32" maple with healed face brs. N.68°W., 26.2'
 BTs mkd- A 10" fir face scribed "NE S29 BT" with X-chop and tag brs. S.53°W., 13.7' to a spike at side center.
 A 12" fir face scribed SE "S20 BT" with X-chop and tag brs. N.68°W., 26.2' to a spike at side center.

Jerry Estabrook - Witness: Pat Coy & Jed Massey - 7/13/2017 - C.S. 65/95-52

 Found - 2" iron pipe with brass cap (properly) marked
 A 48" Fir stump with no visible marks brs. N.35°E., 46.4'.
 A rotten hemlock stump with no visible marks brs. S.01°E., 54.5'.
 A 32" maple with healed face brs. N.68°W., 26.2'.
 A 10" fir face scribed "NE S29 BT" with X-chop and tag brs. S.53°W., 13.7' to a spike at side center.
 A steel fence post brs. N.75°W., 5.0'.
 New BTs- A 12" fir face scribed SE "S20 BT" with X-CHOP and tag brs. N.10°W., 8.3' to a spike at side center.
 continued next page

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 300300

PRIMARY CORNER DESCRIPTION Cor Secs 20, 21, 28, & 29

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

Locations & Comments LAT. AND LONG. PER Garmen Etrex hand
held GPS N: 43°48'40.0" W: 123°54'24.8"
Center of creek bears east 100 feet.
Compass Declination 18° EAST .