

PRIMARY CORNER DESCRIPTION Cor. Secs. 16, 17, 20, & 21

Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____
Alias _____	Description _____

GLO survey by William Thiel under contract 271 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 194)

Set post, in middle of flat gulch, for corner to secs. 16, 17, 20, & 21; from which

- An Alder, 15" dia., bears N.17°W., 40 lks.
- A Chittewood, 6" dia., bears S.84°W., 37 lks.
- A Chittewood, 8" dia., bears N.21°E., 79 lks.
- A Vine Maple, 4" dia., bears S.50°E., 20 lks.

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 238)

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11730)

The cor. of secs. 16, 17, 20, & 21, re-monumented by the county surveyor** with an iron pipe, 1" dia., 14" above ground, firmly in place, from which an orig. BT:

- An Alder, 32" dia., bears N.17°W., 40 lks., with partial scribe marks visible on decayed face of partly opened blaze.


and trees mkd. by the county surveyor

- A Fir, 66" dia., bears N.52°45'E., 200 lks., mkd. on the bark S16 T20S R10W CS BT.
- A Fir, 31" dia., bears S.51°E., 110 lks., with partial scribe marks visible on partly healed blaze.
- An uprooted Fir, 28" dia., the stump hole of which bears S.85°W. 67 lks. w/blaze on trunk marked T20S R10W CS BT

At the corner point

Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

T20S R10W



from which new BTs:

- A Fir, 30" dia., bears N.58½°E., 197 lks., mkd: T20S R10W S16 BT.
- A Fir, 30" dia., bears S.69¼°E., 129 lks., mkd: T20S R10W S21 BT.
- A Cherry, 16" dia., bears S.12½°W., 49 lks. mkd: ¼ S20 BT.

Reset the county surveyor's IP alongside the iron post.

**4/5/1999 I could find no information concerning a renewal by the DCSO, Tracy's 1968 renewal refers to C.S. File 16/58 and to M 1-56 but I do not find any information for this corner. Jean Crawford, Survey Technician, DCSO.

cont.

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 300400

PRIMARY CORNER DESCRIPTION Cor Secs 16, 17, 20, & 21

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

Douglas Co. Surveyors Office - Vernon "Ray" Tracy - Jack Heritage - V. Perron - March 1968 - C.S. File 53/66-81

Found - 1951 GLO brass cap gone.
66" Fir, alive, N.52°45'E., 132.0 ft. bark scribe.
(See C.S. 16/58)**
Orig. 32" Alder, alive, N.17°W., 26.4 ft., blaze decayed out.
30" Fir N.58½°E., 130.0 ft., alive & good condition.
30" Fir s.69½°E., 75.1 ft., alive & good condition.
All other 1951 BTs down.

Set - Brass cap at cor. mkd: COUNTY SURVEYORS OFFICE 1968
T20S R10W
S 17 | S 16
S 20 | S 21

No tree close for new BTs.
This corner lies in head of ravine on NE slope, very steep & brushy.

Fd. Ok by Richard Hintz, April 1983 - M 90-42

Jerry Estabrook - For: Menasha Log Co. LLC & The Campbell Group LLC ITS Manager - May 2012 - M163-55 & C.S. 65/75-5

Found - Brass cap mkd: "COUNTY SURVEYORS OFFICE T20S R10W S16 S17 S20 S21 1968" per Douglas Co.
A 66" fir stump with no visible marks and tag bears N.52¾°E., 132.0'.
A 30" fir stump with healed face and tag bears N.58½°E., 130.0'
New BTs- A 32" triple trunk hemlock face scribed "SW S16 BT" with x-chop and tag bears N.87°E., 89.3' to a spike at side center.
A 31" double trunk maple face scribed "BT" with x-chop and tag bears S.04°E., 59.1' to a spike at side center.
An 11" alder bark scribed "NE S20 BT" with x-chop and tag bears S.20°W., 16.0' to a spike at side center.
An 11" alder bark scribed "NE S20 BT" with x-chop and tag bears S.70°W., 5.9' to a spike at side center.