

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 300540

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 8 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 271 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 197)

Set ¼ sec. post by marking a boulder, 3 ft by 2 by 6 ft. No timber accessible and the rocky nature of the ground not allowing any pits.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11732-3)

The ¼ sec. cor. of secs. 8 & 9, monumented with a sandstone 6x3x2 ft. above ground, with plain chisel marks on SW face. At a point against the W face of the corner stone, ½ lk. from the old chisel marks,
Set an iron post, 3 ft. long, 1" dia., 28" in the ground, with brass cap marked:

¼
S 8 S 9
1952

from which
A Maple, 40" dia., bears N.86°E., 68 lks., mkd: ¼ S9 BT.
A Maple, 16" dia., bears S.65½°W., 52 lks., mkd: ¼ S8 BT.
Chisel a large X on W face of corner stone.

Fd. Ok by Richard Hintz, April 1983 - M 90-42