

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by William Thiel under contract 271 dated Aug. 18, 1877 - (DCSO records Vol. 1 Page(s) 197)

Set post to cor. of secs. 8, 9, 5, & 4, on top of flat ridge; from which

- An Alder, 10" dia., bears N.72°E., 35 lks.
- An Alder, 8" dia., bears N.69°W., 53 lks.
- A Fir, 42" dia., bears S.60°W., 55 lks.
- A Fir, 36" dia., bears S.30°E., 85 lks.

Fd. & used on GLO survey by F. M. Johnson under contract 303 dated Sept. 30, 1878 - (DCSO records Vol. 1 Page(s) 199)

Fd. & used on GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol.1 Page(s) 240-1)

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11733)

The corner of secs. 4, 5, 8, & 9, determined at the record bearing & dist. from each of the orig. BTs, as follows:

- An Alder, 23" dia., bears N.72°E., 35 lks., mkd: S4 T20S R10W BT on the bark.
- A Fir, 56" dia., bears S.30°E., 85 lks., mkd: S9 T20S R10W BT on bark blaze.
- An uprooted Fir, 60" dia., bears S.60°W., 55 lks., with blaze on under side of trunk.
- An Alder, 15" dia., bears N.69°W., 53 lks., mkd: S5 T20S R10W BT on the bark.

At the corner point
Set an iron post, 3 ft. long, 2" dia., 28" in the ground, with brass cap marked:

T20S R10W

S 5	S 4
S 8	S 9
1952	

from which a new BT

- A Fir, 50" dia., bears S.45°45'W., 139 lks., mkd: T20S R10W S8 BT.

Fd. OK by J. Prochnau - 8/1971 (added 7/10/2017) M43-56
Fd. Ok by Richard Hintz - April 1983 - M 90-42

(Cont. next page)

TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 300600

PRIMARY CORNER DESCRIPTION Cor. Secs. 4, 5, 8, & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

James Prochnau - For: Siuslaw National Forest - June 30, 1987
- M 104-51 A & B

Found - A 2½" brass cap on a 2" galvanized iron pipe set by
GLO in 1952, properly stamped.
60" D.Fir stump bears S.30°E., 56.1 ft. (rec.
S.30°E., 85 lks.) healed. (1878 BT)
Alder stump bears N.6°W., 36.7 ft. (rec. N.69°W., 53
lks) 1952 BT
38" D.Fir stump bears S.45°W., 91.7 ft., (rec.
S.45°15'W., 139 lks, healed.
14" Alder bears N.9°E., 30.3' healed. (Unrecorded)
New BTs- 4" Alder bears N.82°W., 43.1 ft. scribed "X BT".
7" Hemlock bears S.57½°W., 23.2 ft. scribed "T20S
R10W S8 BT"
Reference Monument set -
A USFS 2½"x30" alum. pipe with 3¼" alum. cap
stamped: T20S R10W RM S9 1987 PLS 1305