

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 16 & 21

Alias	Description
Alias	Description
Alias	Description
Alias	Description

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 239)

-----  
Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which  
A Maple, 10" dia., bears N.63°E., 71 lks., mkd: ¼ S BT.  
A Maple, 6" dia., bears S.34°W., 69 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11729-30)

-----  
Point for the ¼ sec. cor. of secs. 16 & 21, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 20" in the ground to solid rock, and in a small mound of stone, with brass cap marked:

¼  $\frac{S\ 16}{S\ 21}$   
1952

from which  
An Alder, 16" dia., bears N.62°E., 56 lks., mkd: ¼ S16 BT.  
A Maple, 30" dia., bears S.76½°E., 156 lks., mkd: ¼ S21 BT

Jerry Estabrook - For: Menasha Log Co. LLC & The Campbell Group LLC ITS Manager - May 2012 - M163-55 & C.S. 65/75-5

-----  
Searched for the South ¼ corner of Sec 16. BLM established this corner in 1952 at a midpoint between section corners. The corner falls in a washed out draw. I could not find this corner I therefore establish it at a midpoint between section corners. The draw has been washed out to bedrock on the bottom and sides. This made it impractical to drive an iron rod for a monument. I therefore chopped an X in the rock face at the corner position and set a reference monument and marked bearing trees for the X chop marking the corner.

Set - RM: A 5/8"x30" iron rod with plastic cap marked "Estabrook LS 2703" bears N.84°08'30"E., 43.84' from x-chop marking ¼ corner.

A 10" alder bark scribed "S¼ S16 BT" with x-chop and tag bears N.56°E., 46.8' to a spike at side center.

A 29" fir face scribed "N¼ S21 BT" with x-chop and tag bears S.60°E., 84.1' to a spike at side center.

An 18" fir face scribed "N¼ S21 BT" with x-chop and tag bears S.12°W., 32.0' to a spike at side center.

A 14" alder bark scribed "N¼ S21 BT" with x-chop and tag bears S62°W 7.0' to a spike at side center.

Note- Centerline of draw bears east 15.0'