TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 340500

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 9 & 16

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 240)

Set post, 4 ft. long, 3½" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Fir, 25" dia., bears N.17°W., 66 lks., mkd: ¼ S BT.
A Fir, 15" dia., bears S.29°E., 56 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11731)

Point for the ¼ sec. cor. of secs. 9 & 16, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 9 / S 16 / 1952

from which
A Dogwood, 14" dia., bears N.83°W., 4 lks., mkd: ¼ S9 BT.
A Fir, 48" dia., bears S.77½°W., 39 lks., mkd: ¼ S16 BT.

Fd. Ok by Ronald Stuntzner, Oct. 1970 - C.S. File 55/163

Jerry Estabrook - For: Menasha Log Co. LLC & The Campbell Group LLC ITS Manager - May 2012 - M163-55 & C.S. 65/75-5

Found - A 1" iron pipe with 2½" brass cap marked "¼ S9 S16 1952" in mound of stones. Per BLM
A 48" fir snag with tag and no visible marks bears S.77½°W., 25.7'.
New BTs- 9" fir face scribed "N¼ S16 BT" with x-chop and tag bears S49°E 2.4' to a spike at side center.
A 10" fir face scribed "N¼ S16 BT" with x-chop and tag bears S.54°W. 19.5' to a spike at side center
A 10" fir face scribed "S¼ S9 BT" with x-chop and tag bears N.65°W., 8.4' to a spike at side center