TOWNSHIP 20 RANGE 10 POINT IDENTIFIER # 340600

PRIMARY CORNER DESCRIPTION 1/4 Cor. Secs. 4 & 9

Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____
Alias _____ Description _____

GLO survey by Nathaniel Martin, under contract # 599 dated June 20, 1892 - (DCSO records Vol. 1 Page(s) 241)

Set post, 4 ft. long, 4" sq., 24" in the ground for ¼ sec. cor., mkd: ¼ S on N face; from which
A Hemlock, 9" dia., bears N.33°E., 54 lks., mkd: ¼ S BT.
A Fir, 6" dia., bears S.70°W., 80 lks., mkd: ¼ S BT.

BLM dependent resurvey by Thomas A. Tillman,, under Group # 297, Surveyed May 1951 thru Oct 1952 - (DCSO records Vol. 27 Page(s) 11734)

Point for the ¼ sec. cor. of secs. 4 & 9, at proportionate distance; there is no remaining evidence of the orig. corner. Set an iron post, 3 ft. long, 1" dia., 28" in the ground with brass cap marked:

¼ S 4 / S 9 / 1952

from which
A Maple, 60" dia., bears N.81°W., 16 lks., mkd: ¼ S4 BT.
A Fir, 45" dia., bears S.73¼°E., 181 lks., mkd: ¼ S9 BT.